ELCO Lighting

Project name:

Fixture type:

Date:

2" Ultra Slim LED Gimbal Lights (350 lm)

Eliminates the need for housing

Features

- IC Rated
- For indoor use only
- 5W
- CRI 90+
- 120V
- ETL listed
- ENERGY STAR compliant
- Dimmable Triac/ELV

Specifications

Wattage	5W
Lumens	350 lm
Voltage	120V
Color Temp.	3000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Damp Location	Listed

Options

White **Nickel** **Bronze**

Dimensions



Technical Details

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: Aluminum die-cast trim with durable powdercoat finish preventing rust and paint cracking. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation.

Electrical: Included driver connects directly to 120V power supply. Standard input wattage is 5W, 70 lumens per watt.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatability List.

Listings: ETL Listed for DAMP Locations. ENERGY STAR® Certified. Califonia Title 24 Compliant (JA8-2016-E)

Warranty: 5-year limited warranty.

Product Number

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ERT21830N	LED	350 lm	3000K	5W	120V	Triac/ELV	Nickel

Product Number Builder Example: **ERT21830N**

Round Gimbal Light	Color Temp	Finish
ERT218		
	30 3000K	**W** All White
	40 4000K	**N** Nickel
	CT5 2700K - 5000K	**BZ** Bronze

© ELCO Lighting 2022. All rights reserved • Rev. 16 Feb 2022 • ELCO Lighting reserves the right to make specification and design changes without notice.