ELCO Lighting

Project name:

Fixture type:

Date:

Flexa™ 6" Round Reflector for Koto™ Module

Mix and match any ring finish with any reflector finish

Features

- 2 Piece Flexa™ trims for maximum design flexibility.
- Convenient twist-lock design for ease of installation.
- Diecast construction for lasting quality.
- 7 3/8″ O.D. - 2 1/4" H

Technical Details

Construction: Diecast aluminum with a powder coated finish.

Installation: Twist-lock design allows for easy mounting onto the Koto™ LED Module. Clips securely mount trim into the housing and keeps ring flush with ceiling.

Compatible Module: Koto™ LED Modules (ELK07 & ELK09 Series)

Lamp: Koto™ LED Module.

Options

All White

All Black

All Bronze

Black Reflector w/White Ring

All Chrome

Chrome Reflector w/White Ring

Chrome Reflector w/Nickel Ring

Haze Reflector w/White Ring

Dimensions



Product Number

Item	Finish
ELK610CN	Chrome Reflector w/Nickel Ring

Product Number Builder

Example: **ELK610WW**

2042 E. Vernon Ave., Vernon, CA 90058 • Tel (323) 231-2600 Fax (323) 231-3200 • elcolighting.com
© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.

6" Koto™ Flexa™ Trim	Reflector Finish	Ring Finish
ELK610		
	W White	**W** White
	B Black	**B** Black
	BZ Bronze	**BZ** Bronze
	C Chrome	**C** Chrome
	H Haze	**N** Nickel

© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

For use with **6″ Koto™ Twist-&-Lock Trims**

Koto™ LED Module



Koto™ LED Module
ELK07 - ELK09

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Beam Angle
ELK			
	07 750 lm	**27** 2700K	**(blank)** 38° lens (Standard)
	09 950 lm	**30** 3000K	**-S** 18° lens
		35 3500K	**-N** 25° lens
		40 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK09 Only)	**-FC** 18° - 50° Adjustable (ELK07 Only)



Koto™ LED Module with 5-CCT Switch

Product Number
ELK08CT5

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°

Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L50	Color Shifter

6″ Koto™ Dedicated LED ICA Housings



6″ Standard ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL770ICA	7 ½″ Height
EL760ICA	5 ½″ Height, Shallow



6″ Standard Remodel ICA Housing
Remodel

CAT NO.	SPECIFICATIONS
EL770RICA	7 ½″ Height
EL760RICA	5 ½″ Height, Shallow

2-Hour Fire Rated 6″ ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL76FICA	7 ¾″ Height - Sound Rated
EL75FICAS	6 $^{3}/_{16}$″ Height, Shallow

© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.

Compatible Products

ELCO Lighting

For use with **6" Koto™ Twist-&-Lock Trims**

Koto™ Architectural LED Light Engine



Koto™ LED Light Engine
ELK19 - ELK21

PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
ELK	**19** 750 - 850 lm	**27D** 2700K	**(blank)** 38° lens (Standard)
	21 1100 - 1500 lm	**30D** 3000K	**-S** 18° lens
		35D 3500K	**-N** 25° lens
		40D 4000K	**-W** 60° lens
		SD Sunset Dimming (ELK19 Only)	**-FC** 18° - 50° Adjustable (ELK21 Only)

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°

Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L50	Color Shifter

6" Koto™ Dedicated LED ICA Housings

6" Koto™ Maximum Adjustability ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
E6LK37ICA	7 ½" Height, Triac/ELV, 850 (ELK19) - 1100 (ELK21) lm
E6LK38ICAD	7 ½" Height, 0-10V/Triac/ELV, 850 (ELK19) - 1100 (ELK21) lm

6" Maximum Adjustability High Lumen ICA Housing
Double Wall

CAT NO.	SPECIFICATIONS
E6LK43ICA	7 ¼" Height, 120V, Triac/ELV, 1250 lm
E6LK44ICAD	7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1250 lm
E6LK56ICA	7 ¼" Height, 120V, Triac/ELV, 1500 lm
E6LK57ICAD	7 ¼" Height, 120/277V, 0-10V/Triac/ELV, 1500 lm

12V AC Retrofit Koto™ LED Module



12V AC Retrofit Koto™ LED Module
ELK08

PRODUCT NUMBER BUILDER

Koto™ LED Module	Lumens	Color Temperature	Voltage
ELK	**08** 800 lm	**27** 2700K	**-12** 12V AC
		30 3000K	
		SD Sunset Dimming	

ACCESSORIES

Lens

EP731C	18° Lens
EP732C	25° Lens
EP733C	38° Lens
EP734C	60° Lens

**EP732C, EP733C, EP734C Included*

Reflectors

EP735C	15°
EP736C	25°
EP737C	38°
EP738C	60°



Secondary Optics

L45	Hex Louver
L46	Linear Lens
L47	Spread Louver
L49	Frosted Lens
L50	Color Shifter

© ELCO Lighting 2022. All rights reserved • Rev. 17 Dec 2021 • ELCO Lighting reserves the right to make specification and design changes without notice.