

# Pex™ 3" Square Adjustable Pinhole

Pex™ precision die-cast adjustable trims with twist-&-lock system for easy Koto™ Module installation



## Features



- 3" Square Adjustable Pinhole.]
- 358° Rotation.
- 30° tilt (for EL386ICA), 15° tilt (for EL390 Series).
- Convenient twist-lock design for easy installation.
- Lamp: Koto™ LED Module.
- 4 3/8" Sq.

## Technical Details

**Construction:** Diecast aluminum with a powder coated finish.

**Installation:** Twist-lock design allows for easy mounting onto the Koto™ LED Module.

**Lamp:** Koto™ LED Module only.



**Dimensions:**

## Options



**Black Reflector with White Ring**



**All Black**



**All Bronze**



**Black Reflector with Nickel Ring**



**All White**



**Haze/White Ring**

## Product Number

Item	Finish
ELK3327N	Black Reflector w/Nickel Ring

## Product Number Builder Example: ELK3327W

Pex™ 3" Square Adjustable Pinhole	Finish
<b>ELK3327</b>	

- W** All White
- B** Black Refl. / White Ring
- BB** All Black
- BZ** All Bronze
- N** Black Refl. / Nickel Ring
- H** Haze/White Ring

# Compatible Products



For use with Koto™ System 3" Trims

## Koto™ Commercial Construction LED Light Engine



**ELK19 ELK21**  
Koto™ LED Light Engine

### PRODUCT NUMBER BUILDER

Koto™ LED Light Engine	Lumens	Color Temperature	Beam Angle
<b>ELK</b>	<b>19</b> 850 lm <b>21</b> 1100 lm	<b>27D</b> 2700K <b>30D</b> 3000K <b>35D</b> 3500K <b>40D</b> 4000K <b>SDD</b> Sunset Dimming	<b>(blank)</b> 38° lens (Standard) <b>-S</b> 18° lens <b>-N</b> 25° lens <b>-W</b> 60° lens

### ACCESSORIES

Lens	Reflectors	Hex Louver	Linear Louver	Spread Louver	Clear Lens
<b>EP731C</b> 18° Lens <b>EP732C</b> 25° Lens <b>EP734C</b> 60° Lens	<b>EP735C</b> 15° <b>EP736C</b> 25° <b>EP737C</b> 38° <b>EP738C</b> 60°	<b>L45</b> For a better glare shield	<b>L46</b> For a wide rectangular illumination pattern	<b>L47</b> For a symmetrical broadening of light beams	<b>L48</b> Protective clear glass lens

## 3" Commercial Construction Koto™ Dedicated LED ICA Housings



2-Hour Fire Rated  
3" ICA Housing - 7 1/2" Height  
**New Construction**



3" ICA Shallow Maximum Adjustability Housing - 4" Height  
**New Construction**



3" ICA Housing - 5 1/2" Height  
**New Construction**

CAT NO.	SPECIFICATIONS
ELK39FICA	120V - Triac/ELV
ELK39FICAD	120/277V - 0-10V/Triac/ELV

CAT NO.	SPECIFICATIONS
E3LK76ICA	120V - Triac/ELV
E3LK77ICAD	120/277V - 0-10V/Triac/ELV

CAT NO.	SPECIFICATIONS
E3LK65ICA	120V - Triac/ELV
E3LK65ICA-EM1	120V - Triac/ELV Emergency Battery Back-up (90 min)
E3LK66ICAD	120/277V - 0-10V/ Triac/ELV
E3LK66ICAD-EM1	120/277V - 0-10V/ Triac/ELV Emergency Battery Back-up (90 minute)



3" ICA Housing - 5 1/2" Height  
**Remodel**

CAT NO.	SPECIFICATIONS
E3LK65RICA	120V - Triac/ELV