



45360 TRIMLESS SQUARE FIXED DOWNLIGHT



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

2 7/8"

2 7/8"

Driver

included

Box

WATTS

15W

PRODUCT DIMENSIONS

LUMENS

Up to 1029

4 1/16"

PROJECT:		
TYPE:		
TTPE;		
DATE:		
NOTES:		



2700K . 3000K . 3500K . 4000K . 5000K

CRI

90+

SPECIFICATIONS

LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. Mesh plate included.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for wet location.

DIMENSIONS

- Cut hole: ø2 7/8" x 2 7/8".
- Fixture: ø4 1/16" x 5 9/16"H.

ELECTRICAL

- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~104°F)(-20°C~-40°C).

LIGHT MODULE

- 1 x 15W Integrated LED COB.
- · Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- · Beam angle: 38 degree.
- 27K |30K |35K |40K Kelvin (CCT):
- Delivered Lumen: 853 lm | 917 lm | 993 lm | 1029 lm | 1003 lm

CERTIFICATIONS













ORDERING GUIDE

MODEL	FINISH	
45360-022	Black	
45360-015	White	

ACCESSORIES



45612-012 60" 3 pin Connector



45599-019 **NEW CONSTRUCTION SMASH PLATE** 2 13/16" x 2 13/16"



KELVIN

CCT Selectable

QUICK

CONNECT





2 1/16"

ADJUSTABLE

NO

022- Black

BEAM


ANGLE


38°

DIMMABLE

TRIAC/ELV

015- White







NO IC BOX REQUIRED