

NMRT2

Flanged High Lumen LED Gimbal Multiple Lighting Trim

Source: 15W to 30W LED
900lm to 2500lm per head

Type _____

Project _____

Catalog No. _____

Notes _____

PRODUCT DESCRIPTION

A beautiful enclosed steel face plate. Gimbal regressed 1.5 inch for a clean ceiling appearance. Available in 1, 2 and 3 LED linear configurations. Excellent for flexible general lighting in commercial and architectural applications.

CONSTRUCTION

Trim: The aluminum face plate is a flanged seamless stamped metal. Each LED gimbal adjusts independently at 40° with 350° rotation.

Mounting: Trim includes two "V" torsion springs to mount trim securely to housing.

Trim Style: Trim is available in two styles; 1-1/2" regressed or flat face. Flat face is only available in white finish.

Finish: Flange is available in silver or white finish. Regressed face is available in black, silver or white finish.

ELECTRICAL

Input Voltage: 120V or 120-277V (must specify)

Lumens / Wattage: **L09** = 900lm / 15W; **L15** = 1500lm / 18W; **L25** = 2500lm / 30W

Color Temperature: 2700K, 3000K, 3500K or 4000K

CRI: 90+ CRI

Beam Spread: **(S)** 45° Spot, **(M)** 64° Narrow Flood, **(F)** 79° Flood

Operating Temp.: 0°C to 45°C ambient temperature

Dimming: Triac, ELV or 0-10V dimming (must specify)

[Click Here](#) or check complete dimmer list at www.NoraLighting.com in the "Compatibility" page under "Resources" tab

COMPATIBLE HOUSINGS


CATALOG NO.	DESCRIPTION
NMRG2-11	One-Head Housing
NMRG2-12	Two-Head Housing
NMRG2-13	Three-Head Housing

LABELS AND LISTINGS

- cULus Listed for damp locations
- ENERGY STAR certified
- 5-Year Limited Warranty



PRODUCT IMAGES AND DIMENSIONS



Dimensions	Length (A)
1 Head	9-3/4"
2 Head	18"
3 Head	23-3/4"

Flanged High Lumen LED Gimbal Multiple Lighting Trim

Face Type	Number of Heads	Lumens / Wattage Per Head	Color Temperature	Beam Spread	Face / Flange Finish
NMRT2-1 = Regressed Face	1 = One Head	L09 = 900lm / 15W	27 = 2700K	S = 45° Spot	BW = Black / White
NMRT2-1F = Flat Face*	2 = Two Heads	L15 = 1500lm / 18W	30 = 3000K	M = 64° Narrow Flood	SS = Silver / Silver
	3 = Three Heads	L25 = 2500lm / 30W	35 = 3500K	F = 79° Flood	WW = White / White
			40 = 4000K		

*Flat face available in White/White finish only.

Example: **NMRT2-12L2530SBW** = Two Head Regressed Face Flanged High Lumen LED Gimbal Multiple Lighting Trim, 2500lm / 25W per head, 3000K, 45° Spot, Black Face / White Flange