

Project:

## Purolinear 360 LED Wall Bar Spec Sheet

SKU: 23QSWL244B120PHA    Learn more at:  
<https://sonnemanlight.com/purolinear-360-led-wall-bar>

Description: A system of linear tubes, set within the geometry of surface-mounted cylinder brackets, rotate individually to direct the LED illumination in 360 degrees along their axis. Arranged in a linear pattern or along a single path, the possibilities for compositions are endless and unlimited in scalability. Set on a wall, in line behind a bed, the rotatable luminaires provide the variability of direct or indirect illumination.

Type #:

### Dimensions

Height:	1.25"
Width:	97.25"
Extends:	2.75"
Minimum Extension:	2.75
Maximum Extension:	2.75
Canopy/Backplate/Base:	4.5"
Shape:	Double Linear
Size:	48"
Canopy/Backplate/Base Depth:	0.5

### Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	2
Input Voltage:	120VAC
Wattage:	13
Initial Lumens:	2240
Delivered Lumens:	1600
Color Temperature:	3000K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Outlet Box
Dimming Type:	TRIAC/ELV
Bulb Max Wattage:	13

### Installation

Installation:	Licensed electrician required
---------------	-------------------------------------

### Shade

Shade 1 Material:	Optical Acrylic
-------------------	--------------------

### Available Finishes

Available Finishes: Polished Chrome (.01),  
Satin Black (.25), Satin Chrome (.23), Satin  
White (.03)

### General Listings

Features:	ADA Compliant, Damp Rated
Certification:	C-ETL-US
Color/Finish:	Satin White (.03)
Dark Sky Friendly:	N