



Project:

# Thin-Line Indirect LED Wall Bar Spec Sheet

SKU: 2814.25-4-35    Learn more at:  
<https://sonnemanlight.com/thin-line-indirect-led-wall-bar>

Description:

**A system of minimally scaled LED indirect light wall bars, uplight/downlight wall bars, and pendants.** Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. Indirect configurations reflect light back onto the wall or mounting surface to radiate indirect illumination.



Type #:

## Dimensions

Height:	0.75"
Width:	48"
Extends:	3.5"
Minimum Extension:	3.5"
Maximum Extension:	3.5"
Size:	4'

## Installation

Installation:	Licensed electrician required
Installation Orientation:	Any Orientation

## General Listings

Features:	Damp Rated
Certification:	C-ETL-US
Color/Finish:	Satin Black (.25)

## Electrical Specs

Bulb(s) Included?:	Yes
Bulb 1 Type:	Integral LED
Bulb Quantity:	1
Wattage:	22
Initial Lumens:	1450
Delivered Lumens:	900
Color Temperature:	3500K
CRI:	90
Power Supply Type:	Driver
Power Supply Quantity:	1
Power Supply Location:	Remote
Dimming Type:	TRIAC/ELV

## Shipping

Carton 1 L x W x H:	51" X 7" X 4"
Carton 1 Gross Weight:	4 LBS

## Shade

Shade 1 Material:	Aluminum w/Optical Acrylic
-------------------	----------------------------

## Available Finishes

Available Finishes: Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)