

Project:

## REALS LED Surface Mount Spec Sheet

SKU: 7309.XX.DL.98-WL    Learn more at:  
<https://sonnemanlight.com/real-eds-led-surface-mount>

Description: REALS surface-mounted lights are neatly compact and solidly built. They offer a range of lens variations within the tightly defined geometry of their die-cast rings. Also available as a [Downlight Sconce](#), [Up/Down Sconce](#), [Bollard](#), and [Double Bollard](#).

Type #:



### Dimensions

Height: 3.25"  
Diameter: 5"  
Canopy/Backplate/Base: 5"

### Electrical Specs

Bulb(s) Included?: Yes  
Bulb 1 Type: Integral LED  
Bulb Quantity: 1  
Input Voltage: 120VAC  
Wattage: 10  
Initial Lumens: 1040  
Color Temperature: 3000K  
CRI: 90  
Power Supply Type: Driver  
Power Supply Quantity: 1  
Power Supply Location: Outlet Box  
Dimming Type: TRIAC/ELV  
Bulb Max Wattage: 10

### Installation

Installation: Licensed electrician required

### Shipping

Carton 1 L x W x H: 9" X 9" X 6"  
Carton 1 Gross Weight: 3 LBS  
Fixture Weight: 2

### Shade

Lens Type: Dome Lens  
Shade 1 Material: Frosted White Polycarbonate

### Available Finishes

Available Finishes: Textured Bronze (.72), Textured Gray (.74), Textured White (.98)

### General Listings

Features: Wet Rated  
Certification: C-ETL-US  
Color/Finish: Textured White (.98)  
Dark Sky Friendly: N