

3" Round LED Adjustable Gimbal Insert

ELCO Lighting's inserts are engineered with energy-efficient LED technology that produces even illumination with an incredible 93+ CRI. Designed to be used for New Construction, Remodel, and Retrofit applications, these inserts are rated for a life of 50,000 hours, and meet the Title 24 and Energy Star requirements. Suitable for IC and Non-IC housings manufactured by ELCO or others.




Features

- Fits ELCO 3" Dedicated LED Recessed Housings for New Construction and Remodel.
- Die-Cast construction provides lasting durability.
- 25° tilt, 358° rotation.
- Energy Star Certified
- Title 24 JA8-2019 Compliant
- Life Span of 50,000 hours L70.

Specifications

Wattage	9W
Lumens	640 lm - 700 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K - 3000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	93+
Damp Location	Listed

EL313 & EL313CT3 Dimensions



Technical Details

Optics: Frosted polycarbonate lens diffuses light evenly throughout while reducing glare with LED Array technology.

Construction: For use in IC and non-IC housings. Diecast construction for lasting quality and greater heat dissipation. High quality powder coat finish preventing rust and paint cracking.

Installation: Quick connect for use with ELCO housings EL390ICA, EL390RICA, EL39FICA.

Electrical: Driver connects to 120V power supply. High Efficiency driver with a power factor > 0.9.

LED Technology:

- Extremely accurate color rendering with 93+ CRI.
- Lumen Maintenance of 50,000 hours L70 life based on LM80 standardized test results.
- Superior Thermal Management by utilizing integral heat sink.
- Instant On to Full Brightness.
- No LED pixelation.


Dimmability: Works with 120V Triac and ELV type dimmers . Dims down to 10%. For full list of dimmers refer to the Dimmer Compatibility List.

Listings:

- UL Listed for Damp Location.
- RoHS Compliant.
- ENERGY STAR® Certified.
- Title 24 JA8-2019 Compliant

Warranty: ELCO Products are built to last with a 5-year Limited Warranty.

EL313CT5



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
EL31330W	LED	640 lm	3000K	9W	120V	Triac/ELV	White
EL313CT3W	LED	700 lm	2700K, 3000K, 3500K	9W	120V	Triac/ELV	White
EL313CT5W	LED	700 lm	2700K, 3000K, 3500K, 4000K, 5000K	9W	120V	Triac/ELV	White

Product Number Builder

Example: **EL31330W**

ELCO 3" Round Gimbal Insert

EL313

Color Temp.

30 3000K
CT3 2700K, 3000K, 3500K
CT5 2700K - 5000K

Finish

W White

Compatible Products



For use with 3" LED inserts

3" Dedicated LED ICA Housings



3" ICA Maximum Adjustability Housing
New Construction

CAT NO.	SPECIFICATIONS
EL386ICA	Maximum Adjustability



3" ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL390ICA	
EL390ICA-7	277V
EL390ICA-EM5	Emergency Battery Back-up (90 minutes)



3" ICA Housing
Remodel


CAT NO.	SPECIFICATIONS
EL390RICA	



2-Hour Fire Rated 3" ICA Housing
New Construction

CAT NO.	SPECIFICATIONS
EL39FICA	7 1/2" Height - Sound Rated
EL39FICA-7	277V

3" Accessories



Emergency Battery Backup

CAT NO.	SPECIFICATIONS
KEM-LD5	8W, 120/277V



Fire Cover

CAT NO.	SPECIFICATIONS
FIRECVR	9 3/4" H x 17" O.D.



Fire Enclosure

CAT NO.	SPECIFICATIONS
FIREENCL	20 3/8" L x 14 3/8" W
FIREENCL-S	Shallow, 16" L x 14 3/8" W




Mica Fire Tape

CAT NO.	SPECIFICATIONS
FIRETAPE	3/4" W x 16' L

LED Adjustable Gimbal Insert

PHOTOMETRIC REPORT

Product #: EL31330
 Wattage/Lumens: 8.8W/ 637 Lm
 Luminaire LPW: 72 Lm/W



CANDLE POWER SUMMARY

Degrees Vertical	0°
0	239
5	237
15	228
25	209
35	181
45	147
55	111
65	76
75	43
85	13
90	0.35

ILLUMINANCE AT A DISTANCE

Distance to Target Plane	Footcandles Beam Center	Beam Diameter
4'	14.9	10.1'
6'	6.63	15.2'
8'	3.73	20.3'
10'	2.39	25.4'

ZONAL LUMEN SUMMARY

Zone	Lumens	% Luminaire
0-30°	181.98	28.60
0-40°	293.79	46.20
0-60°	502.65	79.00
0-90°	635.56	99.90