

# 2" Ultra Slim LED Gimbal Lights (350 lm)

Eliminates the need for housing



## Features

- IC Rated
- For indoor use only
- 5W
- CRI 90+
- 120V
- ETL listed
- ENERGY STAR compliant
- Dimmable Triac/ELV

## Specifications

<b>Wattage</b>	5W
<b>Lumens</b>	350 lm - 370 lm
<b>Voltage</b>	120V
<b>Color Temp.</b>	2700K, 3000K, 3500K, 4000K, 5000K - 4000K
<b>Dimmable</b>	Triac/ELV
<b>Lamp Type</b>	LED
<b>CRI</b>	90+
<b>Damp Location Listed</b>	

## Options



White

Nickel

Bronze

## Technical Details

**Optics:** Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

**Construction:** Aluminum die-cast trim with durable powdercoat finish preventing rust and paint cracking. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

**Installation:** Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation.


**Electrical:** Included driver connects directly to 120V power supply. Standard input wattage is 5W, 70 lumens per watt.

**Dimmability:** Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatibility List.

**Listings:** ETL Listed for DAMP Locations. ENERGY STAR® Certified. California Title 24 Compliant (JA8-2016-E)

**Warranty:** 5-year limited warranty.

## Dimensions



## Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ERT21830W	LED	350 lm	3000K	5W	120V	Triac/ELV	White
ERT21840W	LED	370 lm	4000K	5W	120V	Triac/ELV	White
ERT21830N	LED	350 lm	3000K	5W	120V	Triac/ELV	Nickel
ERT21840N	LED	370 lm	4000K	5W	120V	Triac/ELV	Nickel
ERT21830BZ	LED	350 lm	3000K	5W	120V	Triac/ELV	Bronze
ERT21840BZ	LED	370 lm	4000K	5W	120V	Triac/ELV	Bronze
ERT218CT5W	LED	350 lm	2700K, 3000K, 3500K, 4000K, 5000K	5W	120V	Triac/ELV	White

## Product Number Builder Example: ERT21830W

Round Gimbal Light	Color Temp	Finish
ERT218		
	30 3000K 40 4000K CT5 2700K - 5000K	W All White N Nickel BZ Bronze

# Compatible Products

For use with 2" Elm™ Light Engines



## 2" Elm™ New Construction Frames

---



Universal Frame for 2", 4" and 6"  
**Elm System Downlights**  
5 1/2" Height

CAT NO.	SPECIFICATIONS
E246LF1	For 2", 4" and 6"