

4" Floating Adjustable Eyeball Downlight with 5-CCT Switch

The innovative 4" Floating Eyeball offers 360° rotation and a 90° tilt range for added versatility.



Features

- 9W / 780 lm
- IC Rated for direct contact to insulation
- CRI 90+
- 120V
- ETL Listed for damp locations
- CA Title 24 compliant
- Dimmable Triac/ELV

Specifications

Wattage	9W
Lumens	780 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Damp Location Listed	

Options



Technical Details

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: IC rated driver and fixture are tested and approved for direct contact with insulation. Aluminum die-cast trim with durable powdercoat finish preventing rust and paint cracking. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two 7/8" knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation.


Electrical: Included driver connects directly to 120V power supply. Standard input wattage is 9W, 85 lumens per watt. Replaces 75W incandescent.

Dimmability: Works with 120V Triac and ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the ELM System Dimmer Compatibility List.

Listings: ETL Listed for DAMP Locations. IC-Rated for direct contact with insulation. Air Tight certified in accordance with ASTM E283-2004. California Title 24 Compliant (JA8-2016-E)

Warranty: 5-year limited warranty.

Dimensions



Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ERT416CT5W	LED	780 lm	2700K, 3000K, 3500K, 4000K, 5000K	9W	120V	Triac/ELV	White
ERT416CT5BZ	LED	780 lm	2700K, 3000K, 3500K, 4000K, 5000K	9W	120V	Triac/ELV	Bronze

Product Number Builder Example: ERT416CT5W

4" Floating Adjustable Eyeball	Color Temp	Finish
ERT416	CT5 2700K - 5000K	W White BZ Bronze

Compatible Products

For use with 4" Elm™ System Slim Panels




4" Elm™ New Construction Frames



Frame with Hanger Bars
New Construction

CAT NO.	SPECIFICATIONS
E4LF1 (4" Round)	8 ½" L x 6" W x 4 ¼" Opening



Round Mounting Plate
New Construction

CAT NO.	SPECIFICATIONS
EMP4 (4" Round)	13 ¼" L x 6 ¼" W x 4 ⅜" Opening



Universal Frame for 2", 4" and 6" Downlights
New Construction

CAT NO.	SPECIFICATIONS
E246LF1	12 ⅛" L x 7 ⅝" W