

Project name:		
Fixture type:		
Date:		

# 6" LED 120V Round Reflector Insert with 5-CCT Switch

Our 6" LED Recessed Downlights are designed for quick and easy installation without housing for both new construction and remodel applications, gives you the options you are looking for in one fixture. The manual switch allows you to choose between 2700K, 3000K, 3500K, 4000K, or 5000K. IC-Rated for use with direct contact with insulation.




#### **Features**

- IC Airtight for use with direct contact to insulation.
- Designed to fit in plenums as shallow as 3".
- Eliminates the need for housing
- New Construction application requires mounting plate or frame.
- Remodel applications require no additional accessories.
- Wet Location allows for use indoors or outdoors.
- Title 24 JA8-2019 Compliant
- Includes driver and Jbox.

#### **Specifications**

Wattage	12W
Lumens	900 lm
Voltage	120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV
Lamp Type	LED
CRI	90+
Wet Location	Listed

#### **Dimensions**



#### **Technical Details**

 $\textbf{Optics:} \ \ \textbf{Polycarbonate lens diffuses light evenly throughout space with no LED pixelation}.$ 

**Construction:** IC rated driver and fixture are tested and approved for direct contact with insulation. Plenumrated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

**Installation:** Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut-out template provided for accurate hole size for proper trim installation. The maximum hole size should not exceed 6" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Standard input wattage is 12W, 75 lumens per watt. Replaces 75W incandescent.

**Dimmability:** Works with 120V Triac/ELV type dimmers. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatability List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation. Title 24 JA8-2019 Compliant.

Warranty: 5-year limited warranty

#### **Product Numbers**

Item	Lamp type	Lumens	сст	Watts	Voltage	Dimming	Finish
ERT615CT5W	LED	900 lm	2700K, 3000K, 3500K, 4000K, 5000K	12W	120V	Triac/ELV	White

### Product Number Builder Example: ERT615CT5W

6" LED 120V Round Reflector Insert with 5-CCT	Color Temp.	Finish	
Swit			
ERT615	CT5 2700K - 5000K	<b>W</b> White	

# **Compatible** Products



For use with 6" Elm™ System Slim Panels

## 6" Elm™ New Construction Frames



Frame with Hanger Bars
New Construction

CAT NO.	SPECIFICATIONS
E6LF1 (6" Round)	9" L x 6 3/4" W x 6 1/4" Opening



Round Mounting Plates
New Construction

CAT NO.	SPECIFICATIONS
EMP6 (6" Round)	17 1/4" L x 8 3/8" W x 6 1/4" Opening



Universal Frame for 2", 4" and 6" Downlights

New Construction

CAT NO.	SPECIFICATIONS
E246LF1	12 1/s" L x 7 5/s" W