

6" LED Recessed Downlights with 5-CCT Switch

Our 6" LED Recessed Downlights are designed for quick and easy installation without a housing for both new construction and remodel applications, gives you the options you are looking for in one fixture. The manual switch allows you to choose between 2700K, 3000K, 3500K, 4000K or 5000K. IC-Rated for use with direct contact with insulation.




Features

- IC Airtight for use with direct contact to insulation.
- Designed to fit in plenums as shallow as 4".
- Eliminates the need for housing.
- New Construction application optional mounting plate or frame.
- Remodel applications require no additional accessories.
- Wet Location allows for use indoors or outdoors.
- Energy Star Certified.
- Title 24 JA8-2019 Compliant.
- Includes driver and Jbox.

Specifications

Wattage	12W
Lumens	950 lm
Voltage	120/277/347V or 120V
Color Temp.	2700K, 3000K, 3500K, 4000K, 5000K
Dimmable	Triac/ELV, Triac/ELV/0-10V
Lamp Type	LED
CRI	90+
Wet Location	Listed

Dimensions



Technical Details

Optics: Polycarbonate lens diffuses light evenly throughout space with no LED pixelation.

Construction: IC rated driver and fixture are tested and approved for direct contact with insulation. Plenum rated cable connector to connect from module to remote driver box. Isolated driver integrated inside aluminum remote box with two knockouts with slots for pryout.

Installation: Designed for super shallow ceiling plenums without any housing. High strength steel spring clip for easy installation. Hole cut out template provided for accurate hole size for proper trim installation. Maximum hole size should not exceed 4 1/4" for this product. Suitable installation for t-grid and drop ceiling applications.

Electrical: Standard input wattage is 12W, 79 lumens per watt. Replaces 75W incandescent.

Dimmability: Works with 120V Triac/ELV type dimmers. Or 120/277V with 0-10V dimminability on 120/277V and Triac/ELV on 120V side. Dims down to 10%. For full list of dimmers, refer to the Dimmer Compatability List.

Listings: ETL Listed for Wet Locations. IC-Rated for direct contact with insulation. Energy Star Certified. Title 24 JA8-2019 Compliant

Warranty: 5-year limited warranty.

Product Numbers

Item	Lamp type	Lumens	CCT	Watts	Voltage	Dimming	Finish
ERT625CT5W	LED	950 lm	2700K,	12W	120V	Triac/ELV	White
			3000K,				
			3500K,				
			4000K,				
			5000K				
ERT695CT5DXW	LED	950 lm	2700K,	12W	120/277/347V	Triac/ELV/0-10V	White
			3000K,				
			3500K,				
			4000K,				
			5000K				

Product Number Builder Example: ERT625CT5W

6" LED Recessed Downlights	Wattage/Lumen	Color Temp.	Voltage	Finish
ERT6	25 Triac/ELV (120V only) 95 0-10V/Triac/ELV (DX only)	CT5 2700K - 5000K	120V DX 120/277/347V	W White

Compatible Products

For use with 6" Elm™ System Slim Panels




6" Elm™ New Construction Frames



Frame with Hanger Bars
New Construction

CAT NO.	SPECIFICATIONS
E6LF1 (6" Round)	9" L x 6 3/4" W x 6 1/4" Opening



Round Mounting Plates
New Construction

CAT NO.	SPECIFICATIONS
EMP6 (6" Round)	17 1/4" L x 8 3/8" W x 6 1/4" Opening



Universal Frame for 2", 4" and 6" Downlights
New Construction

CAT NO.	SPECIFICATIONS
E246LF1	12 1/8" L x 7 5/8" W