



LLD4B/F13

JOB NAME: _____

DATE: _____

TYPE: _____

DESCRIPTION

New! 4 Tier Dome Top offers wide light spread for wider walkways and parking lots where maximum light is required. Rugged die cast aluminum housings. Threaded, gasketed clear glass globe for durable weatherproofing and easy relamping. 1" long, 1/2" threaded nipple included for easy mounting. 75 watt max. incandescent, 13 watt fluorescent.

SPECIFICATIONS

Globes:

Threaded, gasketed globe protects against weather, garden sprinklers and insects. Clear glass GL 100 globes standard for 4 Tier. Clear glass GL60 globes standard for 3 Tire. GL100 white globes also available for attractive appearance and glare reduction.

Patents:

RAB sensor and fixture designs are protected under U.S. and International Intellectual Property laws

Weight:

0

Housing:

Die cast aluminum housing with powder coat finish

Mounting Stem:

Accessory 12" mounting stem with 1/2" threads on both ends available

Socket:

Medium base porcelain with all copper electrical parts and 20" leads, including a ground lead.

UL Listing:

Suitable for wet locations. Suitable for mounting within 4 feet of the ground

Voltage:

120 volts AC

Dome Top:

Wide light spread for wider walkways & parking lots where maximum light is required. Full Cutoff for narrow walkways & glare free lighting in garden areas

F13:

Compact Fluorescent 13W

Lamps:

Fluorescent lamp supplied. 13 watt quad tube. NPF 120V ballast.GX23-2 base Quad lamps, 120V

Color:

Black

ORDERING INFORMATION

Total Watts	Lamp Type	Lamp Base	Ballast	Starting Amps/ Operating Amps				Input Watts	LAMP ANSI	Initial Lumens	Lamp Hours
				120V	208V	240V	277V				
13	Quad	GX23-2	NPF 120V	0.3				17		860	10000

Factory Installed Options

Add suffix to Catalog Number

Note: Specifications may change without notice

RAB Lighting, Inc. • 170 Ludlow Ave • Northvale, NJ 07647 • Tel: 888 RAB-1000 • Fax: 888 RAB-1232 • www.rabweb.com

© 2007