

**ACCELL  
Timers**

Single-Pole  
15A, 120V/AC; 1800W  
Incandescent/Halogen, Magnetic Low-Voltage, Electronic Low-Voltage,  
Fluorescent, Compact Fluorescent, LED



**FEATURES**

- Perfect for both new construction and retrofit with no neutral required for installation.
- Available in both Hours and Minutes versions.
- Five (5) preset time intervals.
- Easily programmable to alternate time intervals to suit your needs.
- Works with all popular load types: Incandescent/Halogen, Magnetic Low-Voltage, Electronic Low-Voltage, Fluorescent, Compact Fluorescent, and LED.
- Horsepower rated for 1/4 HP motor loads.
- LED indication of time interval selected and countdown.
- Color change faceplate kits available.

**ACCELL Timers**

15A 120V/AC; 1800W; Wire Leads

Description	Color Suffix	Catalog No.
1800W 5-Button Minute Timer with Off, Single-Pole	A, B, BK, GY, LA, V, W	□ <b>PT18M</b> __
1800W 5-Button Hour Timer with Off, Single-Pole	A, B, BK, GY, LA, V, W	□ <b>PT18H</b> __

  cULus Listed to UL60730-1A & 60730-2-7, file no. E325082; certified to CSA E60730-1:02 & E60730-2-9:01; NOM certified



**PT18M**

**Power  
Extenders**


1920W/VA  
Incandescent, Halogen, Magnetic Low-Voltage,  
Fluorescent, Neon/Cold Cathode

**FEATURES**

- Aluminum heat sink with snap-on cover (PI19-W and PF19-W).
- P19-W and PF19-W can be surface- or flush-mounted using 1900 Box and 2-gang raised cover.
- Extends the capacity of dimmers and emulates connected dimmers in dimming range and resolution.
- Low-end trim setting for minimum brightness level.

**Power Extenders**

1920W/VA; Back Wire

Description	Color	Catalog No.	
For Incandescent/Halogen, Magnetic Low-Voltage, Neon Cold Cathode	White	□ <b>P19-W</b>	•
For Dimmable Fluorescent Ballasts, Mark 10® & Tu-Wire® Compatible	White	□ <b>PF19-W</b>	•

 UL Listed to UL508, file no. E123072



**P19-W**

Mark 10 is a registered trademark of Philips Advance; Tu-Wire is a registered trademark of Lutron.

**Color Ordering Information:** For ordering devices, include Cat. No. followed by the color code: A (Almond), B (Brown), BK (Black), GY (Gray), LA (Light Almond), V (Ivory), W (White)

**Dimensional Information:** A-51 – A-52

**Specification Information:** Please visit [www.cooperwiringdevices.com](http://www.cooperwiringdevices.com)

 **NAFTA Compliant:** See page F-21