NSW-671 / NSW-672 / NSW-673 / NSW-674 / NSW-675

Mia Die-Cast Mini LED Step Light (Non-Dimmable)

Source: 1.5W LED

Up to 13lm

PRODUCT DESCRIPTION

Long lasting, energy efficient LED step lights provide illumination for safety around steps, balcony areas, or walkways. Warm white 3000K LED light mimics incandescent sources, but does not build up heat while casting a warm and welcoming glow. Durable cast zinc-magnesium face plates available in two finishes to match almost any decor. Efficient LED light sources are low maintenance, offer 50,000 hour lamp life, and savings over 80% in running costs when compared to 10W incandescent step lights.

FEATURES

- 120-277V Non-Dimmable
- \cdot cULus listed for Wet Location
- · Heavy duty plastic housing
- Twelve LEDs offer a total load of only 1.5W
- \cdot Save over 80% when compared to 10W incandescent step lights
- \cdot Integrated, embedded driver
- \cdot 50,000 hours at 70% lumen maintenance rated life
- $\cdot\,$ No harmful ultra violet light, infrared wavelengths, or light leak
- $\cdot\,$ Available in Bronze, Brushed Nickel, or White finishes
- Five different face plate styles

CONSTRUCTION

Housing: Die-cast aluminum Mounting: Easily installs in a standard single gang junction box. Note: IP65 rating for outdoor applications require watertight junction box and gasket (sold separately)

ELECTRICAL

Input Voltage: 120-277V Lumens / Wattage:

NSW-671/30W: 8lm / 1.5W NSW-672/30W: 13lm / 1.5W NSW-673/30W: 13lm / 1.5W NSW-673/30W: 13lm / 1.5W

NSW-675/30W: 9lm / 1.5W Color Temperature: 3000K

Color Rendering Index: 80+ CRI Dimming: Non-Dimmable

LABELS AND LISTINGS

cULus Listed for Wet Location
5-Year Limited Warranty

Mia Die-Cast Mini LED Step Light (Non-Dimmable)

Face Plate	Color Temperature	Finish
NSW-671 = Horizontal Louver	/30 = 3000K	BN = Brushed Nickel W = White
NSW-672 = Lensed	/30 = 3000K	BN = Brushed Nickel
NSW-673 = Horizontal Shroud		BZ = Bronze
NSW-674 = Vertical Louver		W = White
NSW-675 = Vertical Shroud		

Example: NSW-673/30W - Mia LED Step Light, Horizontal Shroud (Non-Dimmable), 3000K, White finish

Type Project

Catalog No.

Notes

PRODUCT IMAGES AND DIMENSIONS 4-3/6 NSW-671/30 Horizontal Louver 4-3/1 3/6 NSW-672/30 Lensed 4-3/4 1_3/8" NSW-673/30 Horizontal Shroud 0 7' 3∕8" NSW-674/30 Vertical Louver 0 1-1/8" NSW-675/30 Vertical Shroud 120122P1

6505 G TEL 32 I G H T I N G © 2022