PTZ-X20-IP 20X Zoom Full HD Broadcast IP PTZ Camera



Featuring IP streaming technology by H.264 & H.265 High Efficiency Video Coding (HEVC).

Compatible with most IP based controllers.

Offers multiple full video formats.

Outputs 3G-SDI, HDMI, USB 3.0/2.0, & RJ-45 (LAN) as well as online video outputs RTSP/RTMP.

Power Optical Zoom capability up to 20x.



PTZ-X20-IP Full HD Broadcast IP PTZ Camera

Video Image Sensor 1/2.85" Progressive CMOS Lens 20X Optical Zoom F1.5 (Wide) ~ F3.0 (Tele) **Effective Pixels** Horizontal: 1920, Vertical: 1080 **PTZ Pixel Size** 2.13 µm x 2.13 µm Lens Pan: 340° Tilt: -30° ~ +90° Resolution 1080p & 1080i: 1920 x 1080 Pan/Tilt Speed Pan: 0° ~ +120°/s Tilt: 0° ~ +80°/s Resolution/Rate 1080p60/59.94/50/30/29.97/25/24/23.98 Preset 10 positions via controller, 128 positions via serial 720p60/59.94/50/30/25 FOV **IP Rate** 1920 x 1080 @ 1~60 **Standard** 1280 x 720 @ 1~60 1024 x 576 @ 1~60 **SMPTE** SMPTE 292M, SMPTE 424M 640 x 360 @ 1~60 **IP Protocol** TCP/IP, RTSP/RTMP HD-SDI/3G-SDI HDMI Output **Physical Camera Control** RS-232, RJ-45 USB 3.0 & 2.0 **Color Space** 4:2:2 (YCbCr) 10bit **Dimensions** 155mm x 160mm x 170mm / 6.10in x 6.92in x 6.69in Weight 1.35kg / 2.97lbs Min. LUX 0.01 LUX **Power** 6W at 12VDC (+9 - +15VDC) **Function** White Balance Auto, Manual, Sodium, Iridescence, Indoor, Outdoor, One Push, ATW **Focus** Auto, Manual **Shutter Speed** 1 to 1/10,000 Sec.

Package contents









Remote Controller

Camera Mounting Bracket

USB 3.0

Power Adaptor & Cable



