

ReAX IP Control Server

Features

- ❖ ReAX Control Engine
- ❖ IPBaseT Manager Pro
- ❖ 2 HDMI Outputs
- ❖ Two 1Gbps LAN Ports
- ❖ Four USB 2.0
- ❖ Four USB 3.0
- ❖ Fiber Optic Audio Output
- ❖ Mic Input
- ❖ Speaker/Line Out
- ❖ Integrated Wi-Fi
- ❖ SD Card
- ❖ Linux OS
- ❖ Intel i5 Processor
- ❖ 128GB SSD
- ❖ Fanless Design



Introducing the all-new RXS-1, the solution to your AV over IP control needs. Loaded out of the box with Aurora's own IPBaseT Pro Server control software and the new, powerful non-proprietary ReAX™ control engine. Powered by Linux, the RXS-1 All-In-One control system comes packed with an Intel® Core i5 processor, 8GB RAM, an 128GB SSD, and a 5-year warranty.

The RXS-1 is designed to interface with Aurora's AV over IP line of transceiver products. Seamless integration with the VLX and IPX product lines allows for easy setup and faster installations.

Technical Specifications

Model Name	RXS-1
Technical	
Processor	Intel® Core i5-5200U 2.2GHz Dual Core
Memory	8GB RAM
Storage	128GB SSD + SD Card Slot
Graphics	Intel® HD graphics 5500 graphics card (32-bit color depth)
HDMI	Two HDMI 4K30 4:4:4
Audio	Mic, Speaker/Line, Optical
Wi-Fi	300M Internal
USB 2.0	4 Type A
USB 3.0	4 Type A
LAN	Two 1G RG-45
Mechanical	
Housing	Metal enclosure
Dimensions [L x W x H]	22.4 x 17.7 x 4.9cm (8.81" x 6.96" x 1.92")
Weight	1.66kg (3.66 lbs.)
Mounting	Desktop horizontal or Vertical
Power supply	12V 5A DC
Power consumption	60 Watts Max
Operation temperature	0~40°C [32~104°F]
Storage temperature	-20~60°C [-4~140°F]
Relative humidity	20~90% RH [no condensation]

Note: Specifications subject to change without notice.

Important: Read User Guide for full specification.