

HuddleCamHD 10XA

Conference Camera with a Built-in Microphone Array

The HuddleCamHD 10XA is ideal for small to medium sized meeting rooms.

This camera is compatible with every system that accepts USB cameras.

Model Number:

HC10XA-BK (Black)

HC10XA-WH (White)

<http://huddlecamhd.com/10xa/>

KEY FEATURES

- 10X Optical Zoom
- Dual Mic Array
- USB 2.0
- RS232 via USB
- 1920 x 1080p
- 57° Field of View
- Up to 30fps
- 64 Presets
- IR Remote



WHAT'S IN THE BOX

- 10X Zoom USB 2.0 Camera with built-in mic array
- 12V/2.0A DC Power Adapter
- Mounts: Tripod Mount
- USB 2.0 Data Cable (3m)
- IR Remote Control
- User Manual



- 1 Lens**
10X Optical Zoom
- 2 Microphone(s)**
Microphone Array
- 3 IR Receiver(s)**
Receivers IR remote control signal(s)

- 4 Power LED**
Blue LED lights when unit is powered and is dark in Standby mode.
- 5 USB 2.0 Interface**
For video/audio connection to PC (USB 2.0 port) (Compatible with USB 3.0 as a USB 2.0 device)
- 6 DC in 12V Socket**
Only use the Power Adapter supplied with this camera

Image Sensor

| | |
|-------------------|--------------------------------------|
| Video CMOS Sensor | 1/3" CMOS, 2.1 Mega Pixel |
| Resolutions | 1080p-30/25, 720p-30/25, SVGA, VGA |
| Frame Rate | Up to 30fps (MJPEG) |
| Lens Zoom | 10X Optical Zoom f=4.9-49mm F2.0-2.8 |
| Field of view | 7° (tele) to 57° (wide) |

Pan/Tilt Movement

| | |
|---------------|--------------------|
| Pan Movement | ±340° |
| Tilt Rotation | Up: 90°, Down: 30° |
| Presets | 64 Presets |

Electrical Index

| | |
|----------------------|----------------------|
| Power Supply Adapter | 12V DC 2A |
| Input voltage | 12V DC (10.5-14V DC) |
| Input Power | 15W (Max) |

Built-in Audio

| | |
|------------------|--------------------------------------|
| Microphone Array | Dual Mics on front of camera base |
| Pickup Range | 360° up to 16.5 ft (5m) |
| Processing | Advanced Auto Gain and Noise Control |

Physical

| | |
|-----------------------|--|
| Material | Aluminum, Plastic |
| Dimensions (in) | 7.1 W x 5.2 H x 3.1 D (5.5 H w/ tilt) |
| Dimensions (mm) | 180 x 132 x 78 (140 H max w/ tilt) |
| Weight | 1.41 lbs (0.64 kg) |
| Operating Temperature | 32°F to 113°F (0°C to 45°C) |
| Color | Black, White, *Silver; * = Special Order |
| Working Environment | Indoor |

Rear Board Connectors

| | |
|-----------------------------|--|
| Video Interface | USB 2.0 UVC |
| Controller Signal Interface | USB 2.0 Virtual Com Port (VISCA, PelcoD) |
| Controller Baud Rate | 9600, 38400 bps |
| Audio Interface | USB 2.0 Plug and Play |
| Power Supply Interface | DC 12V 1.2A |

Other

| | |
|---------------|-----------------------|
| Mfg. Warranty | 2 Years Parts & Labor |
|---------------|-----------------------|

Quality Management System

| | |
|-----|-------------------------|
| QMS | Certified ISO9001: 2008 |
|-----|-------------------------|