

HAWA Super 250/G • Maximum door weight: 250 kg (550 lbs.) • For glass thicknesses: 8 – 16 mm (5/16" – 5/8") • For 1 and 2 sliding glass doors • Smooth quiet operation • Maintenance-free • Simple installation • Vertical adjustment without removing the glass door • Elegant design of continuous top and bottom glass suspension profile 77 3^{1"} 32 46.5 8 g 45 32 32 52 19 3" 4 98 ± (3 5 5 45 15 15 47 22 35" 50 1 31 32 1 3" Glass height 8 - 16 8 - 16 10 - 12.7 5" - <u>5</u>" 5" - 5" 13" - 1" 2 26 26 58 1 1 32 $2\frac{9}{32}$ 92 92 3 5" 3 5" 34 20 25" 32 28 1 3" 19 25 32 Dimensions in mm Inches are approximate

Dimensional data not binding. We reserve the right to alter specifications without notice.

HAFELE

HAWA Super 250/G

Individual Components

Order Specifications


- Upper track
- Type of lower guide or guide channel
- Door width
- Glass thickness
- Door weight
- Number of running gears (2 per door)
- Number of suspension plates (2 per door)
- Number of track stoppers (2 per door)


	Description	Material	Finish	Length/Qty	Item No.
	Upper track, side-drilled	Steel	stainless	6 m (19' 8 1/4")	942.42.601
	Upper track, with mounting flanges	Steel	stainless	6 m (19' 8 1/4")	942.43.601
	Lower guide channel, pre-drilled	Aluminum	anodized	6 m (19' 8 1/4")	946.03.600
	Connecting pin, notched	Steel	galvanized	_	946.12.090
	Lower guide, with plastic slider and suspension block	-	-	-	946.12.060
	Lower guide, rattle-free, for 8, 10, 12 and 12.7 mm (5/16", 13/32", 15/32" and 1/2") thick glass	-	-	-	940.40.032
513	Floor guide, for bottom support and glass suspension profile	-	_	1 pc.	940.84.037
	Glass suspension profile 'G', 8 – 16 mm (5/16" – 5/8")	Aluminum -	anodized	_ 6.5 m (21' 3 15/16")	942.56.865
			unanodized		942.44.023
	Cover cap for glass suspension/retainer profile	Plastic	anthracite gray	-	942.44.061
Con	Running gear	Wheels: Steel	-	-	942.44.012
	Suspension plate, with suspension bolt M12	_	-	-	942.44.020
R. C.	Track stopper, to be drilled into upper track	Steel	galvanized	-	942.42.041
(b)	Buffer, screw-on type	Rubber	black	_	941.60.051
	Cover cap, for glass suspension profile	Plastic	anthracite gray	-	942.56.029
	Glass holder insert, with M6 x 30 mm (1 3/16") screw	Plastic	_	_	940.84.024

Installation Plan

(included in fitting set), mounting instructions for planning and execution available upon request.

Locks	page 1.357		
Glass edge protection profile	page 1.291		
Finishes	page 1.286		





Dimensions in mm Inches are approximate