








EKU Clipo 16 GPK/GPPK Inside Set

	Item No.
Clipo 16 GPK, for 2 doors	405.82.290
Clipo 16 GPPK, for 2 doors	405.82.291







Note

The complete fitting set is always delivered without top track, glass fixing profile and soft close mechanisms, please order separately.

Set Components

	Description	Material	Finish/Color	Qty.
	Running gear, slides and clips into locking component	Plastic	anthracite	4 pcs.
	Locking component, mounts to glass fixing profile	Plastic	anthracite	4 pcs.
	Floor guide for GPK version	Plastic	light gray	2 pcs.
	Floor guide for GPPK version	Plastic	gray	2 pcs.
	Door stop, mounts to top glass fixing profile on outer door	Plastic	light gray	1 pc.
	Track stopper	Plastic	gray	2 pcs.
	Cover cap for GPPK version, for bottom glass fixing profile	Plastic	anthracite	4 pcs.

Individual Components

	Description	Min. Top Panel Thickness	Material	Color	Length	Qty.	Item No.
	Double top track, surface mounted, for screw mounting	19 mm (3/4")	Aluminum	silver colored anodized,	2.5 m (8' 2 7/16")	-	405.90.962
	Double top track, recessed mounted, for screw mounting	19 mm (3/4")	Aluminum	bright	2.5 m (8' 2 7/16")	-	405.90.972
	Glass fixing profile, top and bottom, for glue mounting	-	Aluminum	silver colored anodized,	2.5 m (8' 2 7/16")	-	405.89.932
	Soft closing mechanism Note One set includes two mechanisms. Two sets are required for dual soft closing of two doors.	-	Plastic	gray	-	1 set	405.10.075
	Knob, Ø10 mm (3/8")	-	Aluminum	anodized	-	-	405.46.910
	Flush pull, Ø30 mm (1 3/16"), to be screwed or glued on	-	Aluminum	anodized	-	-	405.46.900

Dimensional data not binding. We reserve the right to alter specifications without notice.