



Model: SNK-F117e
Model: SNK-F1178e
Model: SNK-F11716e

1U SunView Rackmount 17" LCD Keyboard Console

Features

- The model supports the following interfaces (PS/2, USB, SUN I/O and USB).
- A 17 inch 1280 x 1024 high resolution SXGA TFT color LCD monitor, a membrane switch keyboard and a touch pad with 3 buttons.
- Flat modular construction for 19 inch 1U rack mounting. The 1U drawer pulls out and the display raises up like a notebook computer in use. When not in use, the display folds down and latches closed and the 1U drawer pushes into cabinet easily and smoothly.
- Quick and easy installation. Slide rails are NOT included, available in 3 optional configurations.
- Drawer comes with space to install the 4-port Multi-KVM, in the field.
- Optional built-in 8-, 16-port KVM drawer available (Server Drawer Multi)
 - I/F support: PS/2, USB, SUN I/O, USB
 - On Screen Display (OSD) function
 - In Hot Key Mode, the selection screen is displayed on the monitor. This display lets assign names of PCs and select PCs using the cursor key.
- Both separate-sync and composite sync video signals are supported
- RoHS compliant



SUNVIEW
RACKMOUNT CONSOLES



In use

486 (W) x 1215 (47.9" D) x 370 (H) mm

In cabinet

486 (W) x 685 (26.9" D) x 43(H) mm



I-TECH
COMPANY



Model: SNK-F117e
Model: SNK-F1178e
Model: SNK-F11716e

1U SunView Rackmount 17" LCD Keyboard Console

Part Number		SNK-F117e	SNK-F1178e	SNK-F11716e	
19 inch rack space requirement		1U			
LCD drawer part	LCD display	17 inch SXGA TFT color LCD			
	LCD resolution	1280 x1024			
	LCD supported video signal (H, V sync. signal)	Separate sync. / Composite sync.			
	Keyboard	# of keys	83 keys (US), (other languages: 84 keys (Europe), 87 keys (Japan))		
		I/F	Multi-interface**	PS/2: connected with KVM port	
	Touch Pad	Type	Capacitive touch pad, 3 buttons		
I/F		Multi-interface**	PS/2: connected with KVM port		
KVM part	Supported PC/Server	-	Servers with PS/2, USB, Sun I/O and USB I/F		
	Number of server connections (max. number in cascade connections)	-	8 units (64)	16 units (256)	
	Selection method	-	Hot keys, OSD		
	LED indicator	Power	-	8	16
		Select	-	8	16
	Console Port with interface	Keyboard	-	PS/2 Mini Din 6-pin (female) x1: not connected	
		Mouse	-	PS/2 Mini Din 6-pin (female) x1: to be connected	
		Monitor	-	Mini D-SUB 15P (female) x1: to be connected	
	Supported interface for cascaded server	Keyboard	-	PS/2 keyboard compliant	
		Mouse	-	PS/2 mouse compliant	
		USB	-	USB 1.1 compliant	
		Sun I/O	-	Sun keyboard / mouse compliant	
Server cascade port	-	Mini D-SUB 15P (female) x 8	Mini D-SUB 15P (female) x 16		
OSD modes manual	-	Hot key mode / Auto scan mode			
Auto scan intervals	-	3 / 5 / 10 (default), 20 / 40 / 60 seconds			
General	Power supply	100 to 240VAC			
	Operating environment	15° -35° C/10-80%RH			
	Dimension (main unit)	486 (w) x 685 (d) x 43 (h)mm in storage 486 (w) x 1215 (d) x 370 (h)mm in operation			
	Weight (main unit)	14kg	16kg	16kg	
	Included accessories	User manual (x1), Power cable (x1)			



Model: SNK-F117e
Model: SNK-F1178e
Model: SNK-F11716e

1U SunView Rackmount **17"** LCD Keyboard Console

AC cable	AC Power cable	for 8-, 16-port KVM, all US drawer models*	NC14004-B074 R
	AC Adaptor cable	for 2-**, 4-port KVM, Cat5 Extender	NC14004-B077 R
Drawer I/F cables	PC cable	0.7m	F-PC2
		2.0m	F-PC6
		3.0m	F-PC9
	USB cable	0.7m	F-USB2
		2.0m	F-USB6
		3.0m	F-USB9
	Sun I/O cable (Mini 8 Din Male)	0.7m	F-SUN2
		2.0m	F-SUN6
		3.0m	F-SUN9
Interface cables for KVM built-in console Drawer	PC cable	1.8m	FKVM-PC6
		3.0m	FKVM-PC9
		5.0m	FKVM-PC16
	USB cable	1.8m	FKVM-USB6
		3.0m	FKVM-USB9
		5.0m	FKVM-USB16
	Sun I/O cable (Mini 8 Din Male)	1.8m	FKVM-SUN6
		3.0m	FKVM-SUN9
		5.0m	FKVM-SUN16

Guide Rails	
Standard inside mounted guide rail	MTR-STD
Outside mounted guide rail	MTR-OUT
Side mounted guide rail	MTR-SIDE



www.i-techcompany.com www.i-techcompany.com www.i-techcompany.com www.i-techcompany.com