

GROWCONTROLTM GC-PRO

Complete Cultivation Controller

Features

- (12) 24Vdc Outputs (expandable up to 20 internal, 44 with XO system)
- (2) Analog sensor ports (expandable up to 4)
- (4) 24Vdc Discrete Inputs (for switch sensors)
- Multi-Zone capable; control 1-4 environments
- AgrowTouchTM screen with alarms & trending optional
- Serial port standard; Ethernet port optional
- Security levels with password protection
- Heavy duty powder-coated sheet-metal enclosures
- 3-Year full factory warranty Made in USA

GC-Pro Standard Controls


- (3) Lighting Zones, Hot Fire Prevention w/ separate Day/Night Outputs
- (1) Light Flip Box Control
- (8) Multi-Use Thermostats
- (8) Multi-Use Humidistats
- (2) CO2 Injection w/Boost Timer & Ventilation
- (8) 24-Hour Timers, (8) Standard Cycle-Timers (secs, mins or hrs), (4) 24-Hour Scheduled Cycle Timers,
 - (4) Off-Delay Timers, (4) 24-Hr Cancel Timers, (4) Re-Start Delay Timers, (4) Hour Meters
- (4) 16-Stage Irrigation Valve & Pump Timer Controls
- (2) Nutrient Dosing Zones, 8 stages w/Batch Dosing and 16-week Recipe Scheduler
- (2) Automatic Reservoir Drain & Fill Controls
- (2) pH Dosing Zones with (1) up and (1) down stage each
- Outdoor Weather Station Monitoring & Control
- · High & Low Alarms & Limits, High Temp Lighting Shut-Off

GC-Pro-C Greenhouse Model (no hydroponics controls)

- (4) Lighting Zones
- (8) Vent/Shade/Curtain (VSC) Proportional Controls
- (4) Zones Multi-Stage Temperature & Humidity Control (6 stages of cooling, 2 stages of heating, humidify & dehumidify per zone)


Fee PC Software

- Local or Remote Internet Access
- Full Control of all Features (same as touch screen)
- Password Protected with Login Records
- Graphical Trending; Zoom, Save & Print
- Unlimited Data Logging to .CSV
- Camera Integration & Image Capturing
- · E-Mail Alerts for Alarms
- Easy to Use
- Frequently Updated









Relay Modules Connect the GC-Pro's 24Vdc outputs to Agrowtek's relays to control equipment.

- **RX** Relays feature independently controlled 120V outlets.
- CX Contactors feature simultaneously controlled 120V or 240V outlets (for light banks, fans, etc.)
- RD 'dry contact' relays interface directly with HVAC inputs and existing electrical relay/contactor panels.