

INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0039

issue No.:10

Certificate history: Issue No. 10 (2008-8-6)

Status:

Current

2008-08-06

Page 1 of 4

Issue No. 9 (2008-6-16) Issue No. 8 (2008-4-4) Issue No. 7 (2007-7-5)

Issue No. 6 (2006-12-20)

Applicant:

Date of Issue:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Electrical Apparatus:

Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C ≤ Ta ≤ +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

Date:

managing birottor

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa Rockhead Business Park Staden Lane Buxton Derbyshire SK17 9RZ United Kingdom





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2008-08-06

Issue No.: 10

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way

Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11 : 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety "i

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR: UK/BAS/04/0202

File Reference: 04/0202



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2008-08-06

Issue No.: 10

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2008-08-06

Issue No.: 10

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 10.1

To permit the use of an alternative rechargeable cell Sanyo Type UF553450Z. When this cell is used the apparatus marking is Ex ia IIC T4 (-20°C \leq Ta \leq +65°C).

ExTR: GB/BAS/ExTR08.0128/00

File Reference: 08/0305



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0039

issue No.:9

Certificate history:

Status:

Current

Issue No. 9 (2008-6-16) Issue No. 8 (2008-4-4) Issue No. 7 (2007-7-5)

Date of Issue:

2008-06-16

Page 1 of 4

Issue No. 6 (2006-12-20)

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY United Kingdom

Electrical Apparatus:

Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C ≤ Ta ≤ +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa Rockhead Business Park Staden Lane Buxton Derbyshire SK17 9RZ United Kingdom





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2008-06-16

Issue No.: 9

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0 : 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11 : 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.: IECEx BAS 05.0039

Date of Issue: 2008-06-16 Issue No.: 9

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.: IECEx BAS 05.0039

Date of Issue: 2008-06-16 Issue No.: 9

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 9.1

To permit the use of alternative encapsulants in the hybrids as listed on the appropriate parts lists, the use of an optional alternative model name Gasalarm and the introduction of a new drawing listing the possible model names.

ExTR: GB/BAS/ExTR07.0191/00 File Reference: 07/1070



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0039

issue No.:8

Certificate history:

Status:

Current

Issue No. 8 (2008-4-4) Issue No. 7 (2007-7-5)

Issue No. 6 (2006-12-20)

Date of Issue:

2008-04-04

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Electrical Apparatus: Optional accessory:

Gasman Oxygen or Toxic Gas Detector

Type of Protection:

Intrinsic Safety

Marking:

IECEx BAS 05.0039

Ex la IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

Date:

4 -

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa Rockhead Business Park Staden Lane Buxton Derbyshire SK17 9RZ United Kingdom





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2008-04-04

Issue No.: 8

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon
Oxfordshire
OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacturer's quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety "i"

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:



Certificate No.: IECEx BAS 05.0039

Date of Issue: 2008-04-04 Issue No.: 8

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2008-04-04

Issue No.: 8

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 8.1

To permit the use of an alternative rechargeable cell type ICP653450U.

When this cell is used, the marking becomes Ex ia IIC 170°C (T3) (-20°C \leq Ta \leq +65°C)

ExTR: GB/BAS/08.0076/00 File Reference: 08/0211



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.: IECEx BAS 05.0039 issue No.:7 History:

Issue No. 7 (2007-7-5) Issue No. 6 (2006-12-

20)

Date of Issue: 2007-07-05

Current

2007-07-05 Page 1 of 4

Applicant: Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY United Kingdom

Electrical Apparatus: Optional accessory:

Status:

Gasman Oxygen or Toxic Gas Detector

Type of Protection: Intrinsic Safety

Marking: IECEx BAS 05.0039

Ex ia IIC T4 (-20°C ≤ Ta ≤ +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position: Managing Director

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd. Rockhead Business Park Staden Lane Buxton Derbyshire SK17 9RZ United Kingdom





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2007-07-05

Issue No.: 7

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11 : 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR: UK/BAS/04/0202

File Reference: 04/0202



Certificate No.:

IECEx BAS 05,0039

Date of Issue:

2007-07-05

Issue No.: 7

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2007-07-05

Issue No.: 7

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

a) General Assembly and main PCB changes to accommodate a 1/2AA size cell

b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

Variation 1.3

To permit for all versions:

a) Minor changes to the oxygen and toxic i-modules

b) Various changes to drawings, which affect documentation but do not make any technical change.

IECEX ATR: UK/BAS/05/0256 File Reference: 04/0202

Variation 2.1

To permit various changes to documents and the use of an alternative sensor module known as 'dual toxic'.

IECEx ATR: UK/BAS/05/0256/1 File Reference: 04/0202

Variation 3.1

To permit a change of encapsulant in the hybrid circuits.

IECEx ATR: GB/BAS/ExTR06.0029/00 File Reference: 06/0285

Variation 4.1

To permit the use of alternative model names Oxy-Mate C, Oxy-Mate CR, Toxi-Mate C and Toxi-Mate CR, minor additions to the list of Oxygen and Toxic i-Modules which may be used, and a minor change to Hybrid 1A.

IECEX ATR: GB/BAS/ExTR06.0058/00 File Reference: 06/0425

Variation 5.1

To permit minor changes to drawings, the use of alternative sounders, and the use of an optional alternative CO2 chemical i-module.

EXTR: GB/BAS/ExTR06.0104/00 File Reference: 06/0673

Variation 6.1

To permit minor changes to the desktop charger units with part number C01940 and C01941.

Variation 6.2

When only charging of the apparatus is required, the desktop charger part number C01941 may be replaced by any Crowcon charger with an output ($U_{\rm m}$) of 9V.When both charging and data communication are required, only charger / interface part number C01940 must be used.

ExTR: GB/BAS/ExTR06.0172/00 File Reference: 06/1022

Variation 7.1

To permit minor changes to circuits and various documents.

ExTR: GB/BAS/ExTR06.0177/00 File Reference: 06/0781



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX BAS 05.0039

Issue No.: 6

Status:

Current

Date of Issue:

2006-12-20

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY United Kingdom**

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Signature:

(for printed version)

Date:

Managing Director

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane **Buxton** Derbyshire SK17 9RZ **United Kingdom**





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2006-12-20

Issue No.: 6

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety "i"

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-12-20

Issue No.: 6

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-12-20

Issue No.: 6

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

- a) General Assembly and main PCB changes to accommodate a 1/2AA size cell
- b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

Variation 1.3

To permit for all versions:

- Minor changes to the oxygen and toxic i-modules
- b) Various changes to drawings, which affect documentation but do not make any technical change.

IEAE ATD	File Reference:
I IECEx ATR:	File Reletence.
	0.4.10.000
UK/BAS/05/0256	04/0202
OIGENOIGE	

Variation 2.1

To permit various changes to documents and the use of an alternative sensor module known as 'dual toxic'.

IECEx ATR:	File Reference:
UK/BAS/05/0256/1	04/0202

Variation 3.1

To permit a change of encapsulant in the hybrid circuits.

	The state of the s
IECEX ATR:	File Reference:
I IECEXAIR.	•
GB/BAS/ExTR06.0029/00	06/0285
GB/BAS/EXTINOU.0020/00	

Variation 4.1

To permit the use of alternative model names Oxy-Mate C, Oxy-Mate CR, Toxi-Mate C and Toxi-Mate CR, minor additions to the list of Oxygen and Toxic i-Modules which may be used, and a minor change to Hybrid 1A.

	File Reference:
I IECEx ATR:	File Reference.
	06/0425
GB/BAS/ExTR06.0058/00	06/0429
OB/BAG/EXTITION OF	

Variation 5.1

To permit minor changes to drawings, the use of alternative sounders, and the use of an optional alternative CO2 chemical imposition

File Deference: 06/0673			
I CUTD, CD/DAS/EVTDOK OMOZION PIE KRIERENCE: VOZVOZO	EVTR: GR/BAS/EXTR06.0104/00	File Reference: 06/0673	

Variation 6.1

To permit minor changes to the desktop charger units with part number C01940 and C01941.

Variation 6.2

When only charging of the apparatus is required, the desktop charger part number C01941 may be replaced by any Crowcon charger with an output $(U_{\rm m})$ of 9V.

When both charging and data communication are required, only charger / interface part number C01940 must be used.

OD/DAO/ETD06 0470/00	File Reference: 06/1022
ExTR: GB/BAS/ExTR06.0172/00	File Releience. Our IOZZ
EXTIN. ODIDITOIEXTITOTIC TIES	



INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification Scheme for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX BAS 05.0039

Issue No.: 5

Status:

Current

Date of Issue:

2006-09-18

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY**

United Kingdom

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Signature:

(for printed version)

Date:

Managing Director

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane **Buxton** Derbyshire **SK17 9RZ United Kingdom**





Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-09-18

Issue No.: 5

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park Abingdon

Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-09-18

Issue No.: 5

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-09-18

Issue No.: 5

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

- a) General Assembly and main PCB changes to accommodate a ½AA size cell
- b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

Variation 1.3

To permit for all versions:

- a) Minor changes to the oxygen and toxic i-modules
- b) Various changes to drawings, which affect documentation but do not make any technical change.

IECEx ATR:	File Reference:	
UK/BAS/05/0256	04/0202	

Variation 2.1

To permit various changes to documents and the use of an alternative sensor module known as 'dual toxic'.

IECEx ATR:	File Reference:
UK/BAS/05/0256/1	04/0202

Variation 3.1

To permit a change of encapsulant in the hybrid circuits.

IECEx ATR:	File Reference:	
GB/BAS/ExTR06.0029/00	06/0285	

Variation 4.1

To permit the use of alternative model names Oxy-Mate C, Oxy-Mate CR, Toxi-Mate C and Toxi-Mate CR, minor additions to the list of Oxygen and Toxic i-Modules which may be used, and a minor change to Hybrid 1A.

I IECEx ATR:	File Reference:	
	1 11 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	
GB/BAS/ExTR06.0058/00	06/0425	
	00/01-10	

Variation 5.1

To permit minor changes to drawings, the use of alternative sounders, and the use of an optional alternative CO2 chemical i-module.

EXTR: GB/BAS/ExTR06.0104/00	
Extr: GB/BAS/Extr06.0104/00	File Reference: 06/0673



INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification Scheme for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEx BAS 05.0039

Issue No.: 4

Status:

Current

Date of Issue:

2006-07-13

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY**

United Kingdom

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Managing Director

Position:

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane **Buxton** Derbyshire **SK17 9RZ United Kingdom**



Which



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-07-13

Issue No.: 4

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-07-13

Issue No.: 4

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-07-13

Issue No.: 4

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

- a) General Assembly and main PCB changes to accommodate a 1/2AA size cell
- b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

Variation 1.3

To permit for all versions:

- a) Minor changes to the oxygen and toxic i-modules
- b) Various changes to drawings, which affect documentation but do not make any technical change.

IECEx ATR:	File Reference:	
UK/BAS/05/0256	04/0202	

Variation 2.1

To permit various changes to documents and the use of an alternative sensor module known as 'dual toxic'.

IECEx ATR:	File Reference:
UK/BAS/05/0256/1	04/0202

Variation 3.1

To permit a change of encapsulant in the hybrid circuits.

I IFCFx ATR [.]	File Reference:
I IEGEX ATK.	riie Reference:
OD/DAC/ETD00 0000/00	00/0005
GB/BAS/ExTR06.0029/00	06/0285

Variation 4.1

To permit the use of alternative model names Oxy-Mate C, Oxy-Mate CR, Toxi-Mate C and Toxi-Mate CR, minor additions to the list of Oxygen and Toxic i-Modules which may be used, and a minor change to Hybrid 1A.

IECEx ATR:	File Reference:
GB/BAS/ExTR06.0058/00	06/0425



INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification Scheme for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX BAS 05.0039

Issue No.: 3

Status:

Current

Date of Issue:

2006-04-26

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY**

United Kingdom

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane **Buxton** Derbyshire **SK17 9RZ United Kingdom**





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2006-04-26

Issue No.: 3

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate **does not** indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2006-04-26

Issue No.: 3

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2006-04-26

Issue No.: 3

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

- a) General Assembly and main PCB changes to accommodate a 1/2AA size cell
- b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

Variation 1.3

To permit for all versions:

- a) Minor changes to the oxygen and toxic i-modules
- b) Various changes to drawings, which affect documentation but do not make any technical change.

IECEx ATR:	File Reference:
UK/BAS/05/0256	04/0202

Variation 2.1

To permit various changes to documents and the use of an alternative sensor module known as 'dual toxic'.

File Reference:	
04/0202	

Variation 3.1

To permit a change of encapsulant in the hybrid circuits.

IECEY ATR	Ella Dafamana
I ILOUX ATTA	File Reference:
GB/BAS/ExTR06.0029/00	06/0285



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX BAS 05.0039

Issue No.: 2

Status:

Current

Date of Issue:

2006-03-01

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY**

United Kingdom

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEx BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

lanaging Dilector

Position:

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane **Buxton** Derbyshire **SK17 9RZ United Kingdom**





Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2006-03-01

Issue No.: 2

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2006-03-01

Issue No.: 2

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEx BAS 05.0039

Date of Issue:

2006-03-01

Issue No.: 2

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

- a) General Assembly and main PCB changes to accommodate a 1/2AA size cell
- b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

Variation 1.3

To permit for all versions:

- a) Minor changes to the oxygen and toxic i-modules
- b) Various changes to drawings, which affect documentation but do not make any technical change.

 IECEx ATR:
 File Reference:

 UK/BAS/05/0256
 04/0202

Variation 2.1

To permit various changes to documents and the use of an alternative sensor module known as 'dual toxic'.

 IECEx ATR:
 File Reference:

 UK/BAS/05/0256/1
 04/0202

Annexe:



INTERNATIONAL ELECTROTECHNICAL COMMISSION IEC Certification Scheme for Explosive Atmospheres

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX BAS 05.0039

Issue No.: 1

Status:

Current

Date of Issue:

2005-06-27

Page 1 of 4

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way

Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY**

United Kingdom

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

Position:

Signature: (for printed version)

Date:

Managing Director

R S Sinclair

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane Buxton Derbyshire **SK17 9RZ United Kingdom**



ICHIE



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2005-06-27

Issue No.: 1

Page 2 of 4

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire OX14 1DY

United Kingdom

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety 'i'

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEx ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2005-06-27

Issue No.: 1

Page 3 of 4

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2005-06-27

Issue No.: 1

Page 4 of 4

DETAILS OF CERTIFICATE CHANGES (for issues 1 and above):

Variation 1.1

To permit for the rechargeable version:

a) The use of an alternative rechargeable battery as defined on the G A

Variation 1.2

To permit for the non-rechargeable version:

- General Assembly and main PCB changes to accommodate a ½AA size cell
- b) The use of the following type CR2 cells: Panasonic Power Lithium, GP Photo Lithium, Maxell Photo-Power Lithium, or Energizer Photo Lithium

File Reference:

04/0202

Variation 1.3

To permit for all versions:

IECEx ATR: UK/BAS/05/0256

- a) Minor changes to the oxygen and toxic i-modules
- b) Various changes to drawings, which affect documentation but do not make any technical change.

	*	

Annexe:



INTERNATIONAL ELECTROTECHNICAL COMMISSION **IEC Certification Scheme for Explosive Atmospheres**

for rules and details of the IECEx Scheme visit www.iecex.com

Certificate No.:

IECEX BAS 05.0039

Issue No.: 0

Status:

Current

Date of Issue:

2005-05-04

Page 1 of 3

Applicant:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY United Kingdom**

Electrical Apparatus: Gasman Oxygen or Toxic Gas Detector

Optional accessory:

Type of Protection:

Intrinsic Safety

Marking:

IECEX BAS 05.0039

Ex ia IIC T4 (-20°C \leq Ta \leq +65°C)

Approved for issue on behalf of the IECEx

Certification Body:

R S Sinclair

Position:

Managing Director

Signature:

(for printed version)

Date:

1. This certificate and schedule may only be reproduced in full.

2. This certificate is not transferable and remains the property of the issuing body.

3. The Status and authenticity of this certificate may be verified by visiting the Official IECEx Website.

Certificate issued by:

Baseefa (2001) Ltd.

Rockhead Business Park Staden Lane Buxton Derbyshire **SK17 9RZ United Kingdom**





Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2005-05-04

Issue No.: 0

Page 2 of 3

Manufacturer:

Crowcon Detection Instruments Ltd

2 Blacklands Way Abingdon Business Park

Abingdon Oxfordshire **OX14 1DY United Kingdom**

Manufacturing location(s):

This certificate is issued as verification that a sample(s), representative of production, was assessed and tested and found to comply with the IEC Standard list below and that the manufacture'rs quality system, relating to the Ex products covered by this certificate, was assessed and found to comply with the IECEx Quality system requirements. This certificate is granted subject to the conditions as set out in IECEx Scheme Rules, IECEx 02 and Operational Documents as amended.

STANDARDS:

The electrical apparatus and any acceptable variations to it specified in the schedule of this certificate and the identified documents, was found to comply with the following standards:

IEC 60079-0: 2000

Electrical apparatus for explosive gas atmospheres - Part 0: General requirements

Edition: 3.1

IEC 60079-11: 1999

Electrical apparatus for explosive gas atmospheres - Part 11: Intrinsic safety "i"

Edition: 4

This Certificate does not indicate compliance with electrical safety and performance requirements other than those expressly included in the Standards listed above.

TEST & ASSESSMENT REPORTS:

A sample(s) of the equipment listed has successfully met the examination and test requirements as recorded in

IECEX ATR:

File Reference:

UK/BAS/04/0202



Certificate No.:

IECEX BAS 05.0039

Date of Issue:

2005-05-04

Issue No.: 0

Page 3 of 3

Schedule

EQUIPMENT:

Equipment and systems covered by this certificate are as follows:

The Gasman Oxygen or Toxic Gas Detector is designed to detect the presence of oxygen (deficiency) or toxic gas, give a visual indication of the concentration, and give audible and visual alarms if a preset level is exceeded.

It comprises a battery, a gas sensor head, electronic circuits on printed circuit boards, a liquid crystal display, LED's and a piezo sounder, all contained in a plastic enclosure providing a degree of protection of at least IP20.

Two types are available, one rechargeable, and one non-rechargeable. External contacts are provided for recharging, and for serial data communications.

The sensors are known Oxygen or Toxic i-modules, and the permitted i-modules are listed in the User Manual provided by the manufacturer.

The apparatus must only be recharged or connected to serial communications when in a non-hazardous area, using a Crowcon desktop charger or charger / interface part number C01940 or C01941. In the case of the non-rechargeable apparatus, the charging circuit will have no effect.

The cell in the non-rechargeable apparatus must only be changed when in a non-hazardous area, and replaced only with cell type CR2477.

The apparatus is not designed for use in oxygen enriched atmospheres.

CONDITIONS OF CERTIFICATION: NO

Annexe: