

T3

Portable Gas Detection Equipment



T3

Four gas personal monitor

When lives and property are at risk and you need gas detection equipment that is totally reliable, you need Crowcon. For over 40 years Crowcon has been developing and manufacturing high quality products with a reputation for reliability and technical innovation.

Crowcon provide both single gas and multigas monitors for personal monitoring and portable safety applications providing protection against a wide range of industrial gas hazards. The T3 offers you compliance, robustness and a low cost of ownership in a simple to use solution.



Choosing the portable gas detector for your needs

Single button operation, small size and clear top-mounted display make the T3 a favorite in the market among those working in today's most arduous industrial environments.

Designed with the user in mind, the top mount display, full function data and event logs, audible, visual and vibrating alarms deliver top end performance in a small and lightweight package. Gases include the most common four (carbon monoxide, methane, oxygen and hydrogen sulfide), but also an expanded range: ammonia, ozone, sulfur dioxide, hydrogen filtered carbon monoxide (for steel plants) and IR carbon dioxide (for safe area use only).

Robust

Rugged impact resistant design provides extra shock and vibration protection	Provides protection in the harshest environments
Water and Dust resistant to IP65 and IP67	
Can be submerged in water	

Effective Warning

95 dB audible alarm	Ensures prompt evacuation from hazard zone
Vivid red/blue visual alarm	
Vibrating alarm	

Reliable

Proven sensor technology and software operation	Covers you over an extended shift
Clear calibration-due warning	
Lithium-ion battery provides over 14 hours continuous operation from a single charge with no memory effects	

User friendly

Single button operation for all functions	Can be operated with gloved hands
Top mounted, backlit display of all gas readings, diagnostics and battery life	'At a glance' operating status

Please see the back page for full technical specifications.

T3 Gas Tester



With an increased focus on regular bump testing of gas detection instruments both through regulation and individual company requirements, bump testing has become even more important to ensure safety for users.

The T3 Gas Tester offers a solution that ensures compliance. By checking the sensors respond to a known concentration of gas and utilizing the T3 instrument's internal functionality, it makes it a cost-effective, fast and simple solution.

Bump testing exposes each sensor to a known concentration of gas to confirm that it responds correctly and to ensure that the unit is working correctly. If it is found not to be working, then the T3 Gas Tester flags the need for the instrument to be re-calibrated or serviced.

The T3 Gas Tester allows bump testing of T3 instruments fitted with flammable, oxygen, carbon monoxide, hydrogen sulphide and carbon dioxide sensors. The tester can bump all four gases in the instrument within 60 seconds. Using a fixed flow regulator reduces the cost of testing, allowing approximately 140 bumps per 34L cylinder of quad gas.

Fast and simple to use

Automatic detector recognition	Test indicated automatically
Automatic gas delivery	Confident the correct gas volume has been delivered

Reliable

Rugged and robust	Durability for harsh environments
Maintenance free	Low cost of ownership

Flexible

Wall, desk and DIN rail mountable	User configurable
Suitable for in-field and on-site gas testing	
Stand alone unit	
Fast and simple to use	

Part Ordering Information:

GT-T3-01 T3	Gas Tester Kit 1 (includes tester and 1m inlet tubing)
GT-T3-02 T3	Gas Tester Kit 2 (as Kit 1 plus fixed flow regulator)
GT-T3-03 T3	Gas Tester Kit 3 (as Kit 2 plus gas cylinder holder)

REG01	Fixed flow regulator (0.5 l/min)
AC0510	Gas cylinder holder
C03289	1m inlet tubing

T3 Product Specification:

Size		114 x 71 x 48mm (tapers to 20mm) (4.5 x 2.8 x 1.9ins)
Weight		295g (10.4oz)
Alarms	Audible	95dB multiple alarm sounds allow selection of distinctive tones for different alarm levels
	Vibrating	Internal vibrating alarm
Display		Graphic LCD with backlight, giving simultaneous display for all gas channels. Graphic symbols for battery (with proportional indication of remaining operation time), healthy operation or fault warning. Start up indication when calibration is due, overdue, or service required
Display mode	Normal display	Real time gas concentration levels
	Display recall	Peak readings and TWA
Data logging	Timed datalogging	50 hours at 1-minute data rate (>12,000 data logs of 4 channels)
	Threshold logging	Starts after adjustable preset level
	Event logging	>5,000 events
Battery		Rechargeable Li-ion battery
Operating time		Based on four gas unit with flammable sensor: A 5 hour charge from flat provides at least 10 hours of continuous use. A 12 hour charge provides at least 14 hours of continuous use
Sampling		Diffusion or hand aspirator
Operating temp range*		-20°C to +55°C (-4°F to +131°F)
Humidity		20-90% RH @ 40°C non-condensing
Ingress protection		IP65 and IP67
Approval codes	Europe	ATEX II 2 G Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +55°C) BASEEFA05ATEX0187
	International	IECEx Ex ia d IIC T4 Gb (-20°C ≤ Ta ≤ +55°C)BAS05.0059
	North America	CSA Class I Division 1 Groups A, B, C and D
Safety standards	Europe	EN60079-0, EN60079-11, EN60079-1, 94/9/EC
	North America	CSA22.2, 152
	Operating standards	EN50270, EN50271, EN50104, EN45544, EN60079, IEC61508
PC interface		RS232 connection from interface module in charger RS232/USB converter available
Calibration		Can be routinely calibrated using Portables PC software or Crowcon Checkbox IMH
Accessories		Integral alligator clip
Optional accessories		Universal harness plate, shoulder strap, chest harness, aspirator assembly (flow plate, bulb and 2m/6ft tubing), fixed and telescopic sample probes, and an in-line water trap
Charging options		Single way drop-in charger with UK, EU or US plug or in-line 110V/220V supply Single way drop-in charger with options as above including PC interface 5 way multi-charger with universal power supply Vehicle adapter for in-vehicle charging Universal charger for vehicle, wall and desk mounting with a multi-region plug (supplied with EU/UK/US/Australian inserts) and status indication

*Toxic and oxygen sensors are not rated for continuous operation at high temperatures. Consult Crowcon if operating temperatures are likely to exceed 40°C (104°F) for extended periods

T3 Gas Tester Specification:

Size	125 x 185 x 80mm (4.9 x 7.3 x 3.1ins)
Weight	250g (8.8oz)
Instrument supported	T3
Gases supported	Flammable, CO, O ₂ , H ₂ S and CO ₂
Test time	Typically 30 seconds
Tests performed	Sensor response to gas Visual alarm Audible alarm General pass/ fail indication
Automatic gas delivery	0.5 litres/minute (l/min)
Gas inlet/ exhaust	1/1
Accessories	Tubing, gas cylinder holder, fixed flow regulator

Gases and ranges

Ranges and alarms vary by country and application, these can be configured as required. Each channel can have two instantaneous alarms. Toxic channels also have TWA alarms. Flammable gas calibration is available for methane, propane, butane, pentane, hydrogen and ethylene as standard.

Gas	Range	Typical Alarm (US)
Flammable	0- 100% LEL	10%
Oxygen (O₂)	0-25%	19.5/23.5%
Hydrogen sulfide (H₂S)	0-100ppm	10ppm
Carbon monoxide (CO)	1-500ppm	35ppm
Sulfur dioxide (SO₂)	0-20ppm	2ppm
Ozone (O₃)	0-1ppm	0.1ppm
Ammonia (NH₃)	0-100ppm	25ppm
**Carbon dioxide (CO₂)	0-5%	0.5ppm

** T3 is available in a safe area CO₂ version offering 0-5% carbon dioxide measurement. The CO₂ sensor replaces the flammable option and can be supplied with oxygen and toxic sensors.

Crowcon reserves the right to change the design or specification of the product without notice. Check www.crowcon.com for updates.

www.crowcon.com

UK:
Tel: +44 (0) 1235 557700
Fax: +44 (0) 1235 557718
Email: sales@crowcon.com

US:
Tel: +1 859 957 1039
Toll Free: 800 527 6926
Fax: +1 513 957 1044
Email: salesusa@crowcon.us

NL:
Tel: +31 10 421 1232
Fax: +31 10 421 0542
Email: eu@crowcon.com

SG:
Tel: +65 6745 2936
Fax: +65 6745 0467
Email: sales@crowcon.com.sg

CN:
Tel: +86 (0) 10 6787 0335
Fax: +86 (0) 10 6787 4879
Email: saleschina@crowcon.com

IN:
Tel: +91 22 6708 0400
Fax: +91 22 6708 0405
Email: salesindia@crowcon.com

 **CROWCON**
Detecting Gas Saving Lives