# **STRACEABLE** LIVE®



### TraceableLive® WiFi Datalogging Hygrometer/ Thermometer with Remote Notification

### The simple, efficient, and reliable way to stay connected to your critical environments

- Monitor remotely temperature and humidity—connect to existing WiFi
- Alerts: humidity alarm, connectivity interruption, low battery
- Cloud-based applications-no local software required; web, Android, iOS data visibility
- Receive MOBILE PUSH / E-MAIL / TEXT notifications
- Continuous data transmission & monitoring using SSL encrypted SECURE connection
- Unlimited scalability—use TraceableLIVE® in individual labs or an entire network of facilities
- Multiple point temperature calibration—traceable to NIST
- Requires TraceableLIVE<sup>®</sup> subscription

## CONTROL

Stay Connected—LIVE & Secure remote monitoring wherever you go!



Cat. No. 6520

### The TraceableLIVE® service—Simple and SECURE setup



Purchase Purchase a TraceableLIVE™ Product



Connect

Connect your new device to your exisiting Wi-Fi



Create Create an account on TraceableLIVE.com



Point Point device to your account to begin controlling device



IoT Connectivity Protect your work

=	All Locations		Add Location +
•	All In Alarm		
2	HOUSTON METHODIST SAN JACINTO HOSPITAL		
0	Vaccine Refrigerator - 1st Floor 10000010	1	22.93* 23.38*
0	Vaccine Refrigerator - 2nd Ploer	1	24.30° *
	Vaccine Refrigerator - 3nd Floor 10000014	1	23.33° 23.43°
	TEXAS CHILDRENS PEDIATRICS		
	Vaccine Refrigerator - 1st Floor 10000012	1 2	23.91* *
	YOUR LABORATORY		
	Sensitive Liquids - Refrigerator 1 10000010	1	22.93* 23.38*
	Sensitive Liquids - Petrigenster 2 10000011	1	24.30° *
	Sensitive Liquids - Refrigerator 3 100000014	1	23.33° 23.43°



**Cloud-Based** 

**Secure Data Link** 

### Once the setup is complete you can:

- Set alarm parameters on device remotely
- · View current conditions in your lab anywhere
- Generate data reports in real time
- Assign user access for the whole team

	Cat. No.	Range	Accuracy	Resolution	Probe
	6520	Temperature: 0.00 to 55.00°C (32.00 to 131.00°F)	±0.5°C	0.01°	Ambient Sensor Dongle
		Relative Humidity: 0.0 to 100%	±3% RH mid-range, 5% RH otherwise	0.1%	
	6521	Temperature: 0.00 to 55.00°C (32.00 to 131.00°F)	±0.3°C	0.01°	Humidity/Temperature
		Relative Humidity: 0.0 to 100%	±3% RH	0.1%	sensor 10' cable

#### **Traceable® Certificate**

Multi-point calibration on an individually-numbered Traceable<sup>®</sup> Certificate which assures accuracy from an ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability of measurements to the SI units through NIST or other recognized national measurement institutes (NMI) that are signatories to the CIPM Mutual Recognition Agreement.



Control Company • 12554 Old Galveston Rd. Suite B230 • Webster, Texas 77598 • USA Email sales@control3.com • www.traceable.com

Telephone 281 482-1714 • Fax 281 482-9448