



## Data Logging Sound Level Meter

# Know your noise level and stay in compliance

Get precision sound decibel measurements for product noise certification and reduction applications. Meter conforms to IEC61672-1 Class 2 standards.

## **Features**

- Reliable measurements, guaranteed!
   Precalibrated to NIST-traceable standards.\*
- Get added flexibility with four userselectable ranges from 30 to 130 dB
- Suits a wide range of applications with programmable sample rates and A and C weighting capabilities
- Memory expands up to 32,700 readings
- Easy analysis with data logging software featuring graphical display (included)
- Download data via USB to your PC for analysis later
- Ideal for field use—tripod mountable
- + Save battery life with auto power-off

Precalibrated & Ready to Use!

### **Applications**

- Ideal for OSHA and IEC surveys
- Facilities with industrial machinery or equipment
- Residential or commercial environments

#### Includes

Windscreen, 3.5-mm earphone plug, screwdriver, software, USB cable, batteries, and NIST-traceable certificate with data and uncertainties.

\*Calibration certificate provided by InnoCal®, an ISO17025 accredited laboratory (A2LA certificate 1746.01) offering a broad range of NIST-traceable calibration services.

For recalibration, call 866-466-6225 or e-mail info@innocalsolutions.com. Their full complement of services can be viewed at www.innocalsolutions.com.

## **Specifications**

Range	Low: 30 to 80 dB Medium: 50 to 100 dB High: 80 to 130 dB Auto: 30 to 130 dB
Resolution	0.1 dB
Accuracy	±1.4 dB
Weighting	A and C
Response time	Fast = 125 m/sec, Slow = 1 sec
Functions	Max/Min, hold, data logging, auto power-off
Frequency range	31.5 Hz to 8 kHz
Dynamic range	50 dB
Display update	2 times/sec
Connectivity	USB
Analog output	AC/DC outputs from earphone outlet; $AC = 1 Vrms$ , $DC = 10 mV/dB$
Microphone	1/2 inch electret condenser microphone

**Display:** 4 digit backlit LCD with bar graph **Dimensions (L x W x H):** 9<sup>1</sup>/<sub>4</sub>" x 2<sup>1</sup>/<sub>2</sub>" x 1"

(23.5 x 6.1 x 2.7 cm)

Power: Three AAA batteries (included)



Catalog number	Description
MW-20250-29	Data logging sound level meter



Davis.com

**UNITED KINGDOM** 

Free Phone: 0500-345-300

Phone: 020-8574-7556

ColeParmer.co.uk

#### USA

#### **Cole-Parmer** Toll-free: 800-323-4340 Phone: 847-549-7600 ColeParmer.com

#### CANADA

Toll-free: 800-363-5900 Phone: 514-355-6100 ColeParmer.ca

## Davis Instruments For Calibration, Toll-free: 800-358-5525 InnoCal Phone: 847-327-2000 Toll-free: 866-466-66

Toll-free: 866-466-6225 InnoCalSolutions.com

#### INDIA

Toll-free: 1-800-266-1244 Phone: +91-22-6139-4444 ColeParmer.in

#### INTERNATIONAL CUSTOMERS

Call 847-549-7600 ColeParmer.com/dealers