# (D) DIGI-SENSE THE STANDARD IN PRECISION MEASUREMENT



# **Infrared Thermometers**

# Safely and easily locate hot and cold spots, preventing problems and saving costs

Ergonomic pistol-grip infrared (IR) thermometers provide the precision you need for quick and easy temperature measurements. Noncontact meters safely measure the surface temperature of objects without physically touching the object. Simply aim, pull the trigger, and read the display—reliable measurements couldn't be easier!

## All models feature

- Reliable measurements, guaranteed!
  Precalibrated to NIST-traceable standards.\*
- + Laser sighting helps target the measuring area
- + Large backlight LCD with backlight for easy viewing
- + Adjustable emissivity (except model 20250-04)
- Min/Max readings and data Hold function
- + User-selectable temperature readout in °C or °F
- + Automatic selection range and display resolution
- Trigger lock for continuous scanning of temperatures
- + Auto power-off mode extends battery life

### Additional features for Professional models

- Dual-laser sighting to pinpoint target areas
- Higher distance-to-sight (D/S) ratios for long-distance measurements
- Extended temperature ranges
- Temperature differential and average readings
- + USB interface for data transmission to PC
- + Heavy-duty construction and protective lens cover
- + External type K input for contact measurements
- Internal logging of 100 readings (model 20250-08 only)

### **Applications**

- Agricultural
- Educational
- Food processing
- HVAC

- Industrial
  - Laboratory
  - ♦ R&D
    - Preventive maintenance

\*Calibration certificate provided by InnoCal®, an ISO17025 accredited laboratory (A2LA certificate 1746.01) offering a broad range of NIST-traceable calibration services.

For recalibration, call 866-466-6225 or e-mail info@innocalsolutions.com. Their full complement of services can be viewed at www.innocalsolutions.com.

Description	Infrared thermometers			Professional infrared thermometers	
Catalog number	MW-20250-04	MW-20250-05	MW-20250-06	MW-20250-07	MW-20250-08
Distance-to-sight (D/S) ratio	10:1	12:1	20:1	30:1	50:1
Temperature range (IR)	–4 to 630°F (–20 to 332°C)	–31 to 1000°F (–35 to 537°C)	–31 to 1472°F (–35 to 800°C)	–58 to 3002°F (–50 to 1650°C)	–58 to 3362°F (–50 to 1850°C)
Resolution	0.1°F/C	0.1°F/C 0.1°F/C below 1000°, 1°F/C above 1000°		0.1°F/C below 1000°, 1°F/C above 1000°	
Accuracy (IR)	±2.5 of rdg or ±4.5°F (2.5°C)	±4.5°F (2.5°C) from -58 to 68°F (-35 to 20°C); ±1.0% ±1 of rdg from 68 to 572°F (20 to 300°C); ±1.5% ±1 of rdg from 572 to 1000°F (300 to 537°C)	±4.5°F (2.5°C) from -58 to 68°F (-35 to 20°C); ±1.0% ±1 of rdg from 68 to 572°F (20 to 300°C); ±1.5% ±1 of rdg from 572 to 1472°F (300 to 800°C)	$\begin{array}{c} \pm 5.4^\circ \text{F (3°C) from} \\ -58 \text{ to } 68^\circ \text{F (} -50 \text{ to } 20^\circ \text{C}); \\ \pm 1.0\% \pm 1.8^\circ \text{F (1°C) from} \\ 68 \text{ to } 752^\circ \text{F (} 20 \text{ to } 400^\circ \text{C}); \\ \pm 1.5\% \pm 3.6^\circ \text{F (} 2.0^\circ \text{C}) \text{ from} \\ 752 \text{ to } 1472^\circ \text{F (} 400 \text{ to } 800^\circ \text{C}); \\ \pm 2.5\% \text{ from } 1472 \text{ to } 3002^\circ \text{F} \\ (800 \text{ to } 1650^\circ \text{C}) \end{array}$	±5.4°F (3°C) from -58 to 68°F (-50 to 20°C); ±1.0% ± 1.8°F (1°C) from 68 to 932°F (20 to 500°C); ±1.5% ± 3.6°F (2.0°C) from 932 to 1832°F (500 to 1000°C); ±2.0% from 1832 to 3362°F (1000 to 1850°C)
Response time	<1 sec <300 ms		<150 ms		
Emissivity	0.95 fixed 0.10 to 1.0 adjustable		0.10 to 1.0 adjustable		
Laser (Class II)	Single			Dual	
Min/Max reading	Yes			Yes	
Data Hold	Yes			Yes	
Avg reading	No			Yes	
Temp differential	No			Yes	
High/low alarms	No Yes		Yes		
USB interface	No			Yes, unlimited data transmission	
Data logging	No			No	Yes, 100 internal readings
Type K input	No			Yes, -58 to 2498°F (-50 to 1370°C)	
Dimensions	7" x 3½" x 1½" (17.7 x 8.9 x 3.8 cm)			7½" x 6" x 2¼" (18.9 x 15.2 x 5.7 cm)	
Power	One 9 V battery			One 9 V battery	
Accessories included	Battery and NIST-traceable certificate with data and uncertainties			One type K flexible probe, USB cable, software, tripod, carrying case, battery, and NIST-traceable certificate with data and uncertainties	



#### USA

#### **Cole-Parmer** Toll-free: 800-323-4340 Phone: 847-549-7600 ColeParmer.com

#### CANADA

Toll-free: 800-363-5900 Phone: 514-355-6100 ColeParmer.ca

## Davis InstrumentsFor Calibration,Toll-free: 800-358-5525InnoCal

Phone: 847-327-2000

**UNITED KINGDOM** 

Free Phone: 0500-345-300

Phone: 020-8574-7556

ColeParmer.co.uk

Davis.com

Toll-free: 866-466-6225 InnoCalSolutions.com

#### INDIA

Phone: 91-22-6716-222 ColeParmer.in

#### INTERNATIONAL CUSTOMERS Call 847-549-7600

ColeParmer.com/dealers

Œ