



NEW

HM 50

Portable Handheld Pin Moisture Meter

- Easy To Use
- Compatible with Wood Type 1, Wood Type 2, Plaster & Brick / Concrete
- HOLD Function
- 20 Minute Auto Shut-Off
- 2-Line Display



| Parameter | Material | Detail | Range | Accuracy* |
|-----------|------------------|---|------------|-----------|
| M1 | Wood Type 1 | Birch, Beech, Spruce, Larch, Walnut, Cherry | 10 to 90% | ±1% |
| M2 | Wood Type 2 | Oak, Pine, Maple, Ash, Pine Douglas | 9 to 90% | ±1% |
| M3 | Plaster | N/A | 0.1 to 15% | ±1% |
| M4 | Brick / Concrete | N/A | 0.1 to 15% | ±1% |

Material: ABS

Protection: IP54
Display: 2 Lines

Size: 2.8 x 1.3 x 5.8 in

Weight: 7 oz
(w/ batteries)

| | |
|---------------------|---|
| Conditions of Use | 32°F to 122°F / 0°C to 50 °C In Non-Condensing Conditions 0 to 6550 ft / 0 to 2000 m |
| Storage Temperature | -4°F to 176°F -20°C to 80 °C |
| Power Supply | 4 AAA Batteries LR03 1.5 V |
| Battery Life | 180 Hrs |
| European Directives | 2014/30/EU EMC ; 2014/35/EU Low Voltage ; 2011/65/EU RoHS II ; 2012/19/EU WEEE |

*All the accuracies indicated in this technical datasheet were stated in laboratory conditions, and can be guaranteed for measurements carried out in the same conditions, or carried out with calibration compensation