## **Swivel**

Clamps make it easy to see the displa when measuring current. Be safe and rota the backlit display so you can see it.

Refined test circuit speeds up the respon time so you see your measurement right away.

_			
	Function	Ranges	Best Accuracy Best Resolutio
y	Volts AC	600	1.0%±5 / 0.1
	Amps AC	400	2.0%±5 / 0.1
te ~y	Volts DC	600	1.0%±5 / 0.1
	mVDC	10000	0.5%±5 / 0.1
	μAmps DC	1000	1.0%±5 / 0.1
	Ohms	10000	1.5%±5 / 0.1
	Microfarads	1000	5%±15 / 0.1
	Hz (clamp)	20 to 400	0.5%±5 / 0.1
se	Hz (leads)	20 to 400	0.5%±5 / 0.1
_	°F	-40°F to 2200°F	±1°F* / 0.1
	Continuity	LED and Beeper	
	NCV	LED and Beener	

**Model SC54** 

\* System accuracy (SC54 meter + k-type thermocouple after field calibration)

# **Swivel Clamp** Meter with **Temperature**

**Model SC54** 

**Swivel Clamp** Meter with **Temperature** 

**Model SC54** 



**SC54** 

**Swivel Clamp Meter** with Temperature



# Right Stuff for HVACR

#### **Faster Testing**

The new 10000 count display shows large values and small, without moving the decimal point or changing units. This speeds up the response time and is more intuitive to use. For lower ohms and accessory head use, mVDC and ohms have 2 ranges.

### Rugged Display

Expanded temperature tolerances allow for testing in refrigerators and on rooftops.

New display technology unaffected by temperatures -4°F to 158°F.

#### Bright backlight. Capacitance

Test questionable motor start and run capacitors. Determine when a capacitor needs to be replaced.

#### Swivel Head with Backlight

Read your display even in dark, hard to reach places.

#### Frequency (Hz) Through the Clamp

No more unnecessarily breaking the circuit. Isolate the hot wire and check Hz quick and easy.

## **Connect to Your**

**Accessory Heads** Probe tips are removable so you can connect your Fieldpiece

**Temp You Can Trust** Accurate temperature in fast changing environments.

CE N22675 LISTED



New easy access

LED and Beeper

100 hrs typical alkaline

- temp calibration pot.
- Auto-Power-Off. Microamps for flame
- Low ohm range for motor windings. Read up to 400 amps AC with 0.1A

### Included:

SC54 Clamp Meter ATB1 Thermocouple ADLS2 Silicone Leads ASA2 Gator Clip Leads ANC7 Padded Case





The Amp

Clamp with

Convenience

Rotate the clamp 180°

to see the display easier.

The Clamp Claw grabs the

wire you want to measure.

readings, including those taken

through the clamp. Non Contact

Voltage test warns you when

True RMS AC electrical

there's 24+VAC.

# **Single Range with** 0.1 Resolution

Fieldpiece

SC54

Capacitance (MFD), Frequency, Continuity, Ohms, VAC, VDC,


Temperature, Non-contact V, DC Microamps, AC Amps.

SC54

**Test Tools HVACR Pros Trust** 

- **Faster Action**
- Better Zeroing
  Fixed Decimal\*
  Fixed Resolution\*

Fast and Easy Swive Clamp



Beaded K-Type Thermocouple Plugs Right into the Face

Tidy up with the included wraptab ATB1 thermocouple. No more tangled wires. No adapter to lose.

### **Use the Right Thermocouple** Connect any K-type

Use the optional model ATC1 for fast and accurate pipe temperatures



**Measure More** 

As any pro tech knows, there's more to their job than just electrical testing. Accessory heads measure it all: Superheat, vacuum, CO, and more. Go to www.fieldpiece.com to see all available accessory heads.

www.fieldpiece.com

© Fieldpiece Instruments, Inc 2012