

#### Model SC57

The First ever wireless swivel clamp meter gives you all the rich features you expect plus the ability to send

or receive wireless measurements. Refined test circuitry speeds up the response time so you see your measurement right away.

unction	Range	Best Accuracy/
		<b>Best Resolution</b>
olts AC	600	1.0%±5 / 0.1
Amps AC	400	2.0%±5/0.1
olts DC	600	1.0%±5 / 0.1
Amps DC	1000	1.0%±5 / 0.1
Dhms	10000	1.5%±5 / 0.1
licrofarads	1000	5%±15 / 0.1
lz (clamp)	20 to 400	0.5%±5 / 0.1
lz (leads)	20 to 400	0.5%±5 / 0.1
F -4	0°F to 2200°F	= ±1°F* / 0.1
Continuity	LED and Beeper	
ICV	LED and Beeper	
ligh Voltage	LED and Beeper	
Vireless Rang	ge 1 to 75 feet	
Battery	9V	
Battery Life	100 hrs typical alkaline	
rue RMS	Through Clamp or Leads	

And More:

True-RMS.

Frequency (Hz)

through the clamp.

New easy access

Auto-Power-Off.

Microamps for flame

rectifier circuit.

Low ohm range for

motor windings.

amps AC with 0.1A

Read up to 400

SC57 Clamp Meter

**ET2W Transmitter** 

ATB1 Thermocouple

ANC7 Padded Case

ADLS2 Silicone Leads

ASA2 Gator Clip Leads

resolution.

Included:

temp calibration pot.

## **Right Stuff for HVACR**

\* System accuracy (SC57 meter + k-type thermocouple after field calibration)

#### Swivel Head with **LED Flashlight**

Read your display even in the darkest, hardest to reach places. Faster Testing The new 10000 count display shows large values and small, without moving the decimal point or changing units. This speeds up the response time and is more intuitive to use. For lower ohms and accessory head use, mVDC and ohms

#### Wireless Enabled 😡

have 2 ranges.

Use the included ET2W to connect to accessory heads. A double magnet holds your transmitter and head tight on panels.

#### Wireless Benefits

Send measurements to the model HG3 for various system analysis. Receive indoor wet bulb or outdoor dry bulb measurements from Fieldpiece heads using an ET2W or other wireless enabled device.

#### **Rugged Display**

Expanded temperature tolerances allow for testing in refrigerators and on rooftops. New display technology unaffected by temperatures -4°F to 158°F. Bright backlight.

Capacitance Test questionable motor start and run capacitors. Determine when a capacitor needs to be replaced.

## 





370

© Fieldpiece Instruments, Inc 2012

### Wireless Swivel Clamp Meter with **Transmitter**

# 19

Transmitter

Model SC57

Model SC57





#### **A Clamp Meter** with All of the **Right Stuff**

Rotate the clamp 180° to see the display easier. The Clamp Claw grabs the wire you want to measure. All AC electrical readings, including through the clamp, are True RMS.

Included Transmitte Connects to Your Heads

RIELESS EWALED Fieldplece SC57

SEL

5

Fieldpiece

-----

and Transmitter

# **RIGHT STUFF**

\*



SYNC

TRUE RMS AUTO OFF A JOY MAX TEMP 

\*

