

EC 23

Robust, Economical Transmitter



EC 23 Fixed Transmitter

- Simple to use and extremely economical
- Robust aluminum housing is corrosion resistant and dust-tight
- Many sensors available, including 3 detection ranges for ammonia (NH₃)
- Linear 4 to 20 mA output signal
- 18–24 VDC

GfG Instrumentation

1194 Oak Valley Dr, Ste 20, Ann Arbor MI 48108 USA
(800) 959-0329 • (734) 769-0573 • www.goodforgas.com

EC 23: Reliable and Simple

GfG's EC 23 transmitter for detecting toxic gases in ambient air is an inexpensive gas detection solution for use in a wide variety of today's industrial applications.

Robust housing

The robust aluminum casing protects the transmitter's electronic components from the harshest environments. The corrosion resistant casing protects the electrical components from atmospheric hazards and is dust-tight.

Simple gas detection

The EC 23 is the simplest way to monitor ambient conditions. Simply attach the EC 23 to a GfG controller or a PLC to continuously and efficiently monitor the concentration of hazardous toxic contaminants in air.

The EC 23 is also reverse-wire protected to prevent damage due to incorrect wiring of the device. The power connector has a "quick disconnect" feature to simplify transmitter installation and service.



Gases*	Detection range	Resolution
Ammonia (NH ₃) standard temperatures only (-4 to +105°F)	0 to 100 ppm	1 ppm
Ammonia (NH ₃) standard temperatures only (-4 to +105°F)	0 to 200 ppm	1 ppm
Ammonia (NH ₃) standard temperatures only (-4 to +105°F)	0 to 250 ppm	1 ppm
Carbon monoxide (CO)	0 to 500 ppm	1 ppm
Hydrogen sulfide (H ₂ S)	0 to 100 ppm	1 ppm
Hydrogen sulfide (H ₂ S)	0 to 500 ppm	1 ppm

*Other sensors and ranges available on request

Specifications

Gases (see table for available detection ranges and resolution)

Ammonia (NH₃)
Carbon monoxide (CO)
Hydrogen sulfide (H₂S)

Detection Principle

Electrochemical (EC)

Detection Method

Diffusion

Response Time

Based on sensor

Power Supply

18-24 VDC loop power

Output Signal

Linear, 4–20 mA

Signal Connection

2 shielded wire x 18 AWG <1,000 ft

Humidity Range

15-99% r.H. non-condensing

Optional Accessories

Calibration adapter

Specifications subject to change without notification

Distributed by:



GfG Instrumentation

Tel: (800) 959-0329 or (734) 769-0573
Fax: (734) 769-1888
E-mail: info@gfg-inc.com
Website: www.goodforgas.com

Rev. 3 (3/18/14)