

TS400

Daily Bump Testing Made Simple



TS400 Test Station

- **Fully automatic** functional bump test
- **Automatic** test of alarms
- **Automatic** charging option
- **Automatic** record keeping
- Store bump test records for easy retrieval and report generation
- Up to 2,000,000 records in memory
- Economic use of test gas
- Simple pass / fail indication
- Saves time, gas and effort for **lower cost of ownership**

GfG Instrumentation

1194 Oak Valley Dr, Ste 20, Ann Arbor MI 48108 USA
(800) 959-0329 • (734) 769-0573 • www.goodforgas.com

TS400 Test Station for G450 and G460 Detectors

Easy operation

The operation of the **TS400** test station couldn't be any easier. Simply place the G450 or the G460 in the station and the system will take over from there. The **TS400** automatically performs a full functional test that includes performance of all sensors and alarms.



Extensive diagnostics

The **TS400** is designed to go beyond the traditional basic bump test and includes sensor diagnostics tests such as T_{50} and T_{90} . After all, what good is a sensor that can respond to gas when it takes too long to get there? With the **TS400** you can have confidence with this added level of safety.

Charging option

The **TS400** is available (optionally) for use as a charger as well as a test station. After all tests have been completed you may remove and begin using the detector or leave it in the **TS400** for recharging.



Record Keeping

A good gas detection instrument maintenance program is not complete without equally good record keeping. Whether you choose to download the records, maintain the records on a PC / network or your preference is to leave the work to the test station, the **TS400** is the right choice.

The **TS400** can retain as many as 2 million complete diagnostics in memory with the maximum memory installed. That is over 50 years of data even if testing 100 detectors every single day!

Reduced cost of ownership

The **TS400** is designed to reduce the cost of ownership every step of the way. The push button regulator helps to sharply reduce the amount of gas required to test your instruments.

PC communication

The **TS400** comes complete with USB interface cable and download software. The SD card may also be downloaded using a standard SD card reader.

Maintenance certificates

The **TS400** software includes a module to quickly print official bump test certificates. Simply download the records from the **TS400** and start the "Certificate Generator" ... it takes only seconds!

GfG Instrumentation											
Certificate											
G450											
Serial Number: 12345678											
Version: 3.11											
Sensor			Alarm Settings				Test Results				
Sensor	Unit	Alarm 1	Alarm 2	Alarm 3	STEL	TWA	Test	Zero	Gas		
O2	PPM	15	30	0	15	10	30	PASS	PASS		
CO	PPM	35	300	0	200	35	200	PASS	PASS		
O2	%VOL	19.5	17	23.5	0	0	18	PASS	PASS		
LEL	%LEL	10	20	60	0	0	50	PASS	PASS		
									Audible Alarm: PASS		
									Visual Alarm: PASS		
<small> Test performed by: GfG TS400 Test Station Xyz, Inc. Service S/N: 08040059 Version: 2.08 </small>											
						Technician: _____		Date: 2008-06-14		Date: _____	
						Time: _____		Time: 11:25			

Detector with Pump

The **TS400** is available for use with the instrument only or there is an available design for use with the instrument with a pump. There is no need to remove the pump before placing the detector in the test station.

Specifications

Physical Properties	Operation	Standard Accessories
Dimensions: 3.5x4.7x6.3 in (90x120x160 mm) Weight: 10.58 ounces (300 grams) Power: Direct power via USB connection or 12 VDC wall cube or 12 VDC vehicle power (optional)	Interface: G450/G460 keypad Display: G450/G460 graphic display Time stamp: Automatic/Real-time clock	*TS400 data software USB computer interface cable Power supply (only with charging option) 1 GB SD memory card *Configuration software *Download software *Certificate generator
Test Protocol	Gas Connections and Pump	
Gas Response: Automatic bump test Response Time: T_{50} or T_{90} tests Alarm Activation: Time to activate alarm-1 and alarm-2 Visual Alarm: Automatic LED test Audible Alarm: Automatic horn test	Inlets: 1 Gas Outlets: 1 Gas exhaust Flow rate: 0.5 liter per minute	* System requirements: Windows operating system.
	Other Specifications	Optional Accessories
	Temperature range: 50-90°F (10-32°C) Warranty: 1 Year	Push button regulator 2 GB SD memory card 12 VDC vehicle power adapter

Distributed by:



GfG Instrumentation

Tel: (800) 959-0329 or (734) 769-0573
 Fax: (734) 769-1888
 E-mail: info@gfg-inc.com
 Website: www.goodforges.com

Rev. 6 (3/17/14)