

Gasurveyor 500 Series



The GMI Gasurveyor 500 series is the most flexible range of gas detectors available today.

By simple selection of hardware and software options, you can easily configure the product to suit your exact application.

- Measures flammable, oxygen and toxic gases
- Dual mode operation - Combustible Gas Indicator (CGI) / Confined Space Monitor (CSM)
- Rechargeable or alkaline battery options
- Approved to European and North American safety standards
- Extremely robust anti-static case
- Simple to use
- Built-in sampling pump as standard
- Large LCD with automatic backlighting in low level light conditions
- Compatible with the GMI range of Auto Calibration Systems
- Audible / visual alarms for all gas ranges
- Fault alarms for low flow, low battery etc.
- Probes for a wide range of applications



www.gmiuk.com

Detection, Protection, Innovation

GMI. CONFIDENCE WHERE SAFETY IS CRITICAL. Gas Measurement Instruments designs, manufactures and markets a wide range of the highest quality proven personal portable and fixed gas monitoring systems. GMI is an international brand with a worldwide network of distributors and dedicated service centres ensuring fast and effective turnaround on instrument calibration and repair. Our uncompromising engineering excellence, established in over half a century of leadership, enables us to meet the exacting demands of industries where safety is critical. By building and maintaining strong relationships with our customers, GMI understands the unique challenges of the diverse markets we serve. Today, our proud heritage of pioneering gas leak monitors and detectors is shaping the future of GMI.

Gasurveyor 500 Series

In the Gasurveyor 500 range of instruments, GMI offer highly accurate and reliable gas detection instrumentation in an extremely robust, anti-static case. The following table allows you to select the 500 series instrument features to suit your specific needs. If you require further information please contact GMI.

GASURVEYOR 500 MODELS															
SENSORS	511	512	521	522	523	524	525	526	531	532	533	534	536	541	542
0-100% LEL	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
0-100% Gas	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
0-1000ppm CH4		X		X		X		X		X		X	X		X
0-25% O2			X	X					X	X	X	X		X	X
0-200ppm H2S					X	X			X	X			X	X	X
0-1000ppm CO							X	X			X	X	X	X	X

All models have Alarms and Datalogging enabled in Confined Space Mode (CSM).

TECHNICAL SPECIFICATIONS	
Dimensions:	180 (7.1) x 95 (3.7) x 105 (4.1) mm. (in.)
Weight:	1.7 (3.75) kg. (lb.)
Display:	LCD with automatic backlighting
Operating Temperature:	-20°C to +50°C (-4°F to +122°F)
Humidity:	0-95% RH Non-Condensing
Construction / Protection Rating:	Moulded polypropylene case protected to IP54
Sampling System:	Integral pump with flow fail sensor; sample path protected by hydrophobic filter and auto pump switch off.
Power Supply:	4 'D' size Alkaline Cells or Rechargeable Battery Pack
Battery Life:	Alkaline: Approx. 15 hours runtime (NiCd) Rechargeable: Approx. 9 hours runtime
Alarms:	Highly visible flashing LED Sounder: In excess of 80 dB(A), typically 85 dB(A)@ 1m
Response Time: (typical)	LEL Flammable: 3 secs (t ₉₀); 5 secs (t ₉₀) Oxygen: 7 secs (t ₉₀) Toxics: 15 secs (t ₉₀)
Approvals:	EEEx iad IIC T4 Gb II 2G UL Class 1 Groups A, B, C and D MED 0038/YY IEC Ex iad IIC T4 Gb (Ta=-20°C to +50°C) CSA Class 1 Groups ABCD C22.2 No. 152
Standards:	EN50014 / EN50018 / EN50020 / UL913

ORDERING INFORMATION AND ACCESSORIES		
44511/44511R	Gasurveyor 511 (Alkaline)	(Rechargeable)
44512/44512R	Gasurveyor 512 (Alkaline)	(Rechargeable)
44521/44521R	Gasurveyor 521 (Alkaline)	(Rechargeable)
44522/44522R	Gasurveyor 522 (Alkaline)	(Rechargeable)
44523/44523R	Gasurveyor 523 (Alkaline)	(Rechargeable)
44524/44524R	Gasurveyor 524 (Alkaline)	(Rechargeable)
44525/44525R	Gasurveyor 525 (Alkaline)	(Rechargeable)
44526/44526R	Gasurveyor 526 (Alkaline)	(Rechargeable)
44531/44531R	Gasurveyor 531 (Alkaline)	(Rechargeable)
44532/44532R	Gasurveyor 532 (Alkaline)	(Rechargeable)
44533/44533R	Gasurveyor 533 (Alkaline)	(Rechargeable)
44534/44534R	Gasurveyor 534 (Alkaline)	(Rechargeable)
44536/44536R	Gasurveyor 536 (Alkaline)	(Rechargeable)
44541/44541R	Gasurveyor 541 (Alkaline)	(Rechargeable)
44542/44542R	Gasurveyor 542 (Alkaline)	(Rechargeable)
13184	Simple 'low cost' Charger c/w Universal Plug	

All above instruments are supplied with: Harness, 4mm Hex Driver, User Handbook, 1.5m Clear Sample Line, Carrying Case, Standard Probe, Probe Handle Assembly, Sample Line Adaptor, 2 Packs of Cotton Filters.

GASURVEYOR 500 SERIES SENSOR SPECIFICATIONS		
RANGES	GAS	RESOLUTION
0 to 100% LEL	flammable	0.1%(0 - 9.9%) 1% (10 - 100%)
0 to 100% VOL	flammable	1%
0 to 25%	oxygen	0.1%
0 to 1000 ppm	carbon monoxide	1 ppm
0 to 100 ppm	toxics	1 ppm



© 2008 Gas Measurement Instruments Ltd.



Gas Measurement Instruments Ltd

Gas Measurement Instruments Ltd.

Inchinnan Business Park
Renfrew
PA4 9RG
Scotland
Tel: +44 (0) 141 812 3211
Fax: +44 (0) 141 812 7820
sales@gmiuk.com
www.gmiuk.com

GMI Service and Calibration Division

25 Cochran Close
Crownhill
Milton Keynes
MK8 0AJ
Tel: +44 (0) 1908 568 867
Fax: +44 (0) 1908 261 056
service@gmiuk.com
www.gmiuk.com

Gasurveyor 500 Series product brochure Part No. 99405
Issue 5 - 16/02/11

Distributed by:

As an ISO 9001 approved company, Gas Measurement Instruments quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.