**GMI** 

# Gascoseeker® Acclaim



The Gascoseeker® Acclaim is a portable gas detector designed to provide reliable service to general Gas Industry applications at very low cost.

# **FEATURES**

- LOW COST
- EASY TO USE
- **LOW MAINTENANCE**
- LEL / VOL GAS RANGES
- **UP TO 70 HOURS BATTERY LIFE**
- M BARHOLE RECORDS
- AUTO CALIBRATION / INSTRUMENT MANAGEMENT SYSTEM COMPATIBLE
- FULLY CERTIFIED TO INTERNATIONAL STANDARDS



GMI - PROTECTING ENVIRONMENTS . . . WORLDWIDE



#### **SPECIFICATION**

# Measuring Ranges

Flammable (LEL / VOL)

	Range	Resolution	Accurac
LEL	0 to 100%	1%	± 3%
VOL	0 to 100%	1%	± 2%

## **Physical Properties**

7.1ins. (180mm.) x 3.7ins. (95mm.) x 3.9ins. (100mm.)

Weight: 2.5lbs. (1.2kg.) with alkaline batteries

#### Environment

Operating Temp: -4°F to 122°F (-20°C to 50°C) Humidity: 0 to 95% RH

# Construction

Moulded polypropylene case protected to IP57

#### Display

Digital / Analogue

#### Sampling System

Standard Product is hand aspirated. Optional version includes integral sampling pump.

# **Power Source**

Two (2) or Four (4) 'D' size alkaline cells, or

Four (4) rechargeable 'D' size (NiMH) batteries.

#### Typical Sensor Life

Flammable (LEL / VOL): 5 Years

#### Certification

ATEX ( II 2G EEx iad IIC T3 / T4 (pending)

(ii) UL Class | Div 1 Groups C and D T4. -4°F ≤ Tamb ≤ 122°F (-20°C ≤ Tamb ≤ 50°C).



# **Ordering Information**

Distributor

Description Part No.

INSTRUMENT ONLY
Gascoseeker Acclaim (without pump)
Gascoseeker Acclaim (c/w integral pump)

Part No.

47100

47101

Note: Instruments are supplied c/w: Harness; 4mm. Hex Driver; 5ft. (1.5m.) Clear Tubing; User Handbook; Calibration Certificate; Configuration Report; Aspirator Bulb (supplied with 47100 only).

- Batteries are not included

#### INSTRUMENT C/W CASE & ACCESSORIES

Gascoseeker Acciaim	4/102	- 175
(without pump)		
Gascoseeker Acclaim	47103	
(c/w integral nump)		

Note: Instruments are supplied in a Carrying Case c/w. Harness; 4mm. Hex Driver; 5ft. (1.5m.) Clear Tubing; 14ins. (35cm.) Solid End Probe; Probe Handle; Sample Line Adaptor; Cotton Particulate Filters (2 x Box of 10); User Handbook; Calibration Certificate; Configuration Report; Aspirator Bulb (supplied with 47102 only). - Batteries are not included

#### ACCESSORIES

Carrying Case	47085	
Carrying Harness	12370	
14ins. (35cm.) Solid End Probe	12480	
28ins. (70cm.) Solid End Probe	12393	
Flexible Sample Probe	42399	
Probe Handle c/w Filters	12481	
Cotton Filters (2 x Box of 10)	10077	
Carbon Filter (Box of 5)	13937	
Sample Line Adaptor	12688	
Clear Sample Line x 4ft.10ins.	12712	
(1.5 metres) approx.		
Aspirator Bulb	12290	
4 'D' Size Alkaline Batteries	47278	
4 Rechargeable (NiMH) Batteries	47279	
Manual Calibration System IRDA Adaptor c/w Software	14679	
Automatic Gas Delivery System (GDU-2) c/w Software & 6mm. fitting	14605 js	
Automatic Gas Delivery System (GDU-2) c/w Software and 1/4 in. fitti	14606	
Note: For other sampling probes and acce	ssories.	

As an ISO 9001 approved company, GMI Ltd's quality assurance programmes demand the continuous assessment and improvement of all GMI products. Information in this leaflet could thus change without notification and does not constitute a product specification. Please contact GMI or their representative if you require more details.

Copyright @ Gas Measurement Instruments Ltd. 2007. All rights reserved.





contact GMI Ltd.

Q 09760

GMI Ltd. - Head Office Inchinnan Business Park, Renfrew, PA4 9RG Scotland. UK. Tel: +44 (0) 141-812 3211 Fax: +44 (0) 141-812 7820

www.gmluk.com e-mail: sales@gmluk.com

GMI USA - Head Office San Diego, California, USA, Tel: +1 760 631 0922 Fax: +1 760 631 1427

www.gmlusa.net e-mail: sales@gmlusa.net

GMI PROTECTING ENVIRONMENTS ...
WORLDWIDE