

#### **MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS**

## PRODUCT NAME: BUTANE (0.001%-0.9%) IN AIR

MSDS NO: 17		Version:3	Date: March, 2012		
1.	Chemical Product and Company Identification				
	Gasco Affiliates, LL 320 Scarlett Blvd. Oldsmar, FL 34677	.c			
	TELEPHONE NUME FAX NUMBER: (866 E-MAIL: info@gasc	5) 755-8920	24-HOUR EMERGENCY NUMBER: 1-800-424-9300		
	PRODUCT NAME: E CHEMICAL NAME: COMMON NAMES/ TDG (Canada) CLAS WHIMIS CLASSIFIC	SYNONYMS: None SSIFICATION: 2.2	AIR		

2. **COMPOSITION/ INFORMATION ON INGREDIENTS** 

INGREDIENT	%VOLUME	PEL-OSHA	TLV-ACGIH	LD <sub>50</sub> or LC <sub>50</sub> Route/Species
Butane FORMULA: C <sub>4</sub> H <sub>10</sub>	0.001-0.9	Simple Asphyxiate	800 PPM	LC <sub>50</sub> 658 g/m <sup>3</sup> /4H (rat)
AIR FORMULA: Mixture	Mixture	N/A	N/A	N/A

#### HAZARDS IDENTIFICATION 3.

EMERGENCY OVERVIEW Compressed gas-Nonflammable. Product contains sufficient oxygen to support combustion.

#### ROUTE OF ENTRY:

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
Yes	No	Yes	Yes	No
HEALTH EFFECTS:				
Exposure Limits	Irritant	Sensitization	Reproductive Hazard	Mutagen
No	Yes	No	No	No
Carcinogenicity:NTP: No IARC: No OSHA		A: No		

# EYE EFFECTS:

N/A

SKIN EFFECTS: N/A



## **MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS**

## PRODUCT NAME: BUTANE (0.001-0.9%) IN AIR

#### **INGESTION EFFECTS:**

Ingestion unlikely. Gas at room temperature.

#### INHALATION EFFECTS:

Due to the small size of this cylinder of gas, no unusual health effects form over-exposure are anticipated under routine circumstances of use.

NFPA HAZARD CO	DDES	HMIS HAZARD CODES		RATING SYSTEM	
Health: Flammability: Reactivity:	0 0 (4 as Butane) 0	Health: Flammability: Reactivity:	0 0 (4 as Butane) 0	0= No Hazard 1= Slight Hazard 2= Moderate Hazard 3= Serious Hazard 4= Severe Hazard	

#### 4. FIRST AID MEASURES

EYES: N/A

**SKIN:** N/A

#### INGESTION:

Not required

#### INHALATION:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASED OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED THE SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh AIR. Quick removal from the contaminated area is most important. If breathing has stopped administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

## 5. FIRE-FIGHTING MEASURES

These containers hold gas under pressure, with no liquid phase. If involved in a major fire, they should be sprayed with water to avoid pressure increases, otherwise pressures will rise and ultimately they may distort or burst to release the contents. The gases will not add significantly to the fire, but containers or fragments may be projected considerable distances - thereby hampering fire-fighting efforts.

## 6. ACCIDENTAL RELEASE MEASURES

In terms of weight, these containers hold very little contents, such that any accidental release by puncturing etc. will be of no practical concern.

## 7. HANDLING AND STORAGE

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Use only in well-ventilated areas. Do not heat cylinder by any means to increase rate of product from the cylinder. Do not allow the temperature where cylinders are stored to exceed 130°F (54°C).

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Use adequate ventilation for extended use of gas.



#### **MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS**

## PRODUCT NAME: BUTANE (0.001-0.9%) IN AIR

### 9. PHYSICAL AND CHEMICAL PROPERTIES

PARAMETER:
Physical state
Evaporation point
pH
Odor and appearance

VALUE: : Gas : N/A : N/A : Colorless, odorless gas

#### 10. STABILITY AND REACTIVITY

Stable under normal conditions. Expected shelf life 48 months.

## 11. TOXICOLOGICAL INFORMATION

No toxicological damage caused by this product.

#### 12. ECOLOGICAL INFORMATION

No ecological damage caused by this product.

#### 13. DISPOSAL INFORMATION

Do not discharge into any place where its accumulation could be dangerous. Used containers are acceptable for disposal in the normal waste stream as long as the cylinder is empty and valve removed or cylinder wall is punctured; but GASCO encourages the consumer to return cylinders.

#### 14. TRANSPORT INFORMATION

	United States DOT
PROPER SHIPPING NAME:	Compressed Gas N.O.S.
	(Butane in Air)
HAZARD CLASS:	2.2
IDENTIFICATION NUMBER:	UN1956
SHIPPING LABEL:	NON-FLAMMABLE GAS

Canada TDG Compressed Gas N.O.S. (Butane in Air) 2.2 UN1956 NON-FLAMMABLE GAS

#### 15. REGULATORY INFORMATION

Butane is listed under the accident prevention provisions of section 112(r) of the Clean Air Act (CAA) with a threshold quantity (TQ) of 10,000 pounds.

#### 16. OTHER INFORMATION

This MSDS has been prepared in accordance with the Chemicals (Hazard Information and Packaging for Supply (Amendment) Regulation 1996. The information is based on the best knowledge of GASCO, and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for other purposes than it is intended.

#### MSDS/S010/17/ March, 2012