

MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT NAME: HEXANE (0 – 0.48%) IN AIR

MSDS NO: 262 Date: March, 2012 Version:3

1. **Chemical Product and Company Identification**

Gasco Affiliates, LLC 320 Scarlett Blvd. Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

24-HOUR EMERGENCY NUMBER: 1-800-424-9300

FAX NUMBER: (866) 755-8920 E-MAIL: info@gascogas.com

PRODUCT NAME: HEXANE (0- 0.48%) IN AIR

CHEMICAL NAME: Hexane in air **COMMON NAMES/ SYNONYMS: None** TDG (Canada) CLASSIFICATION: 2.2 WHIMIS CLASSIFICATION: A

2. **COMPOSITION/ INFORMATION ON INGREDIENTS**

INGREDIENT	%VOLUME	PEL-OSHA	TLV-ACGIH	LD ₅₀ or LC ₅₀ Route/Species
Hexane FORMULA: C ₆ H ₁₄	0 to 0.48%	500 ppm TWA	50 ppm	N/A
Air FORMULA: Mixture	99.52 to 99.999%	N/A	N/A	N/A

HAZARDS IDENTIFICATION 3.

EMERGENCY OVERVIEW

This product is a colorless gas mixture which is either odorless or has a faint solvent like odor. Hexane can cause anesthetic or peripheral neuropathy effects.

ROUTE OF ENTRY:

Skin Contact	Skin Absorption	Eye Contact	Inhalation	Ingestion
No	No	No	Yes	No
HEALTH EFFECTS:				
Exposure Limits	Irritant	Sensitization	Reproductive Hazard	Mutagen
No	Yes	No	Yes	No

Carcinogenicity: --NTP: No IARC: No OSHA: No

EYE EFFECTS:

N/A

SKIN EFFECTS:

N/A



MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT NAME: HEXANE (0 - 0.48%) IN AIR

INGESTION EFFECTS:

Ingestion unlikely. Gas at room temperature.

INHALATION EFFECTS:

Due to the small size of this cylinder, no heath hazards are anticipated if used in normal circumstances. Irritations of the respiratory tract, nausea and headache have been observed at 1,500 ppm Hexane. Dizziness and drowsiness can occur at 5,000 ppm. Long term over-exposure can result in a numbing sensation of the fingers and toes. More serious exposures can cause damage to the nerves in the hands and feet (peripheral neuropathy).

NFPA HAZARD	CODES	HMIS HAZARD	CODES	RATING SYSTEM	
Health: Flammability: Reactivity:	1 0 0	Health: Flammability: Reactivity:	1 0 0	0= No Hazard 0= Slight Hazard 2= Moderate Hazard 3= Serious Hazard 4= Severe Hazard	

4. FIRST AID MEASURES

EYES:

N/A

SKIN: N/A

INGESTION:

Not required

INHALATION:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASED OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED THE SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. If breathing has stopped administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

5. FIRE-FIGHTING MEASURES

These containers hold gas under pressure, with no liquid phase. If involved in a major fire, they should be sprayed with water to avoid pressure increases, otherwise pressures will rise and ultimately they may distort or burst to release the contents. The gases will not add significantly to the fire, but containers or fragments may be projected considerable distances - thereby hampering fire fighting efforts.

6. ACCIDENTAL RELEASE MEASURES

In terms of weight, these containers hold very little contents, such that any accidental release by puncturing etc. will be of no practical concern.

7. HANDLING AND STORAGE

Suck back of water into the container must be prevented. Do not allow backfeed into the container. Use only properly specified equipment which is suitable for this product, its supply pressure and temperature. Use only in well-ventilated areas. Do not heat cylinder by any means to increase rate of product from the cylinder. Do not allow the temperature where cylinders are stored to exceed 130°F (54°C).



MATERIAL SAFETY DATA SHEET - CALIBRATION CHECK GAS

PRODUCT NAME: HEXANE (0 - 0.48%) IN AIR

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Use adequate ventilation for extended use of gas.

9. PHYSICAL AND CHEMICAL PROPERTIES

PARAMETER: VALUE:
Physical state : Gas
Evaporation point : N/A
pH : N/A

Odor and appearance : Colorless, odorless or faint solvent like odor

10. STABILITY AND REACTIVITY

Stable under normal conditions. Expected shelf life 48 months.

11. TOXICOLOGICAL INFORMATION

No toxicological damage caused by this product.

12. ECOLOGICAL INFORMATION

No ecological damage caused by this product.

13. DISPOSAL INFORMATION

Do not discharge into any place where its accumulation could be dangerous. Used containers are acceptable for disposal in the normal waste stream as long as the cylinder is empty and valve removed or cylinder wall is punctured; but GASCO encourages the consumer to return cylinders.

14. TRANSPORT INFORMATION

United States DOT Canada TDG

PROPER SHIPPING NAME: Compressed Gas N.O.S. Compressed Gas N.O.S.

(Hexane in Air) (Hexane in Air)

HAZARD CLASS: 2.2 2.2 UN1956 UN1956 UN1956

SHIPPING LABEL: NONFLAMMABLE GAS NONFLAMMABLE GAS

15. REGULATORY INFORMATION

Hexane is subject to the reporting requirements of CFR 29 1910.1000. This chemical is listed on Table Z.1. **U.S. TSCA INVENTORY STATUS**: The components of this gas mixture are listed on the TSCA Inventory.

16. OTHER INFORMATION

This MSDS has been prepared in accordance with the Chemicals (Hazard Information and Packaging for Supply (Amendment) Regulation 1996. The information is based on the best knowledge of GASCO, and its advisors and is given in good faith, but we cannot guarantee its accuracy, reliability or completeness and therefore disclaim any liability for loss or damage arising out of use of this data. Since conditions of use are outside the control of the Company and its advisors we disclaim any liability for loss or damage when the product is used for other purposes than it is intended.

MSDS/S010/262/ March, 2012