

Features :

1. Water Proof
2. On / Off Switch
3. Polycarbonate Case
4. Stainless Steel Probe
5. Automatic power off after 10 minutes
6. Data Hold Function
7. °C or °F switchable
8. Stirring-purposed probe cover

Specifications :

Measurement Range	: -50°C to 280°C / -58°F to 536°F
Accuracy	: ±1°C between -20°C to 120°C ±2°C between -20°C to -50°C & 120°C to 150°C ±4°C between 150°C to 200°C ±6°C between 200°C to 280°C ±2°F between -4°F to 248°F ±4°F between -4°F to -58°F & 248°F to 302°F ±8°F between 302°F to 392°F ±11°F between 392°F to 536°F
Resolution	: 0.1° between -19.9° to 199.9° Otherwise 1°
Sampling time	: 0.5 second
Battery	: 1.5 volt type LR44 or equivalent x 1 pc
Battery life	: 5000 hours
Ambient temperature	: -10 to 50°C or 14 to 122°F

Operation :

1. Press [ON/OFF] to switch on.
2. Probe into test substance about 50mm (2")
3. Press [°C/°F] at the rear case to select the temperature unit, OR Press [HOLD] to retain reading [°C or °F flashing], then Press [HOLD] again to release & take instant temperature reading,
4. Press [ON/OFF] to switch off.

Battery Replacement :

1. Loosen the 4 screws at the rear case and replace the battery
2. Close the rear cover by tighten the 4 screws

Caution :

1. Make sure tightening up all screws after battery replacement, otherwise, it maybe affected the waterproof function.
2. Not to use inside the oven

