

# GENERAL<sup>®</sup>

## THE SEEKER<sup>™</sup> 400 Wireless Video Recording Inspection System

**A Wireless, Video Recording Digital  
Camera Scope for the Visual Inspection  
of Inaccessible Areas**



No. DCS400

FC CE

### Applications:

- Ideal for: Automotive, Plumbing, Construction and Restoration, HVAC/R, and any other Inspection of Hard-To-Reach and Hard-To-See Areas

### Features:

- 12mm (0.47 in.) diameter probe, 1m (3.28 ft.) long, flexible-obedient and waterproof to IP67 standards
- Optional probe extensions of 1m, 2m, and 3m (3.28 ft., 6.56 ft., 9.84 ft.) are available to extend probe length up to 5m (16 ft.)
- 3.5 in. (88.9mm) diagonal TFT-LCD Wireless Color Monitor can be detached from the unit for remote viewing up to 32 ft. (10m) away
- 4x zoom feature
- 180° image flip feature
- Both monitor and handle use rechargeable "li-ion" batteries which can be charged at the same time using the included one-into-two charging cable
- System comes complete with batteries and charger
- Two adjustable LED lights inside the tip of the probe illuminate dark spaces for clear inspection
- View results in real-time, record video and capture/save still photos (JPEG). Up to 3 hours of video (AVI)
- NTSC or PAL compatible
- USB and video interconnect cables are included
- Built-in magnets and stand facilitate hands-free operation
- Choice of 5 menu languages: English, French, Spanish, Chinese and Portuguese
- Comes with 45° mirror, magnetic pick-up and pick-up hook accessories for probe tip

### Specifications:

#### CAMERA/PROBE:

- Transmission Range:** Up to 10m (32.8 ft.) clear field
- Transmission Frequency:** 2.4GHz
- Resolution:** 320 x 240 Pixels (NTSC)  
704 x 576 pixels (PAL)
- Depth of Field (DOF):** 30 to 100mm (1.2 to 3.94 in.)
- Field of View:** 60°
- Camera Tipped Probe:** 12mm (.47 in.) diameter
- Probe Length:** Standard 1m (3.28 ft.)
- Optional 12mm Probe Extensions:**  
1m, 2m, 3m (3.3 ft., 6.6 ft., 9.9 ft.)
- Dimensions:** 215 x 165 x 50mm (8.5 x 6.5 x 1.9 in.)
- Weight:** 425g (15 oz.)
- Power Source:** 1 "li-ion" rechargeable battery (included)

#### DETACHABLE, WIRELESS MONITOR:

- Display:** 3.5 in. (88.9mm) diagonal TFT LCD Color Screen
- Resolution:** 320 x 240 Pixels
- Video/Image Resolution:** 320 x 240 Pixels (AVI)
- Dimensions:** 100 x 85 x 25mm (3.9 x 3.3 x 1.0 in.)
- Weight:** 172g (6.1 oz.)
- Power Source:** 1 "li-ion" rechargeable battery
- CE/FCC Approvals:** Yes



### Includes:

- Custom Hard Case
- Pistol Grip Camera Handle
- 12mm Diameter, 1m (3.3 ft.) Long Flexible-Obedient Probe
- Detachable, Wireless Monitor
- 2GB Micro SD Memory Card
- 3 Accessory Tools: (45° Mirror, Magnetic Pick-Up, Pick-Up Hook)
- 1 Mini-Screwdriver
- USB and Video Interconnect Cables
- Built-in Magnets
- 2 "li-ion" Rechargeable Batteries with AC Adapter/Charger
- Instruction Manual
- Three Year Limited Warranty

# GENERAL<sup>®</sup>

**General Tools & Instruments**

80 White Street, New York, NY 10013-3567  
TEL: 212. 431. 6100 TOLL FREE: 800. 697. 8665  
sales@generaltools.com www.generaltools.com

Printed in USA 8/10 2.5M DCS400SS