Nickel High Range Handheld Colorimeter

Nickel is extensively used in electroplating, the manufacturing of steel, electronic devices, ceramics and colored glasses. It plays a vital role in many processes of applied sciences and fundamental sciences. It necessitates development of rapid methods for estimation of nickel

Nickel is seldom found in natural waters, but often present in industrial wastewater as a direct by-product of metal plating baths, and as a corrosion by-product of stainless steel, nickel or cobalt alloys.

The most serious effects of nickel, such as lung cancer and nasal sinus have occurred in people who have breathed nickel dust while working in nickel refineries or in nickel processing plants. The levels of nickel in the workplace were much higher than background levels. The Department of Health and Human Services has determined that nickel and certain nickel compounds may be reasonably anticipated to be carcinogens. The International Agency for Research on Cancer (IARC) has determined that some nickel compounds are carcinogenic to humans and that metallic nickel may possibly be carcinogenic to humans. The EPA has determined that nickel refinery dust and nickel subsulfide are human carcinogens. Other lung effects including chronic bronchitis and reduced lung function have been observed in workers breathing nickel.

The HI 726 Checker®HC is extremely simple to use. First, zero the instrument with your water sample. Next, add the reagent, shake gently until complete dissolution. Last, place the vial into the Checker®HC, press the operational button for about 3 seconds. The display will show the countdown prior to the measurement or, alternatively, wait for 1 minute and press operational button. When the timer ends the meter will perform the reading and display concentration in q/L of nickel. It's that easy.

ORDERING INFORMATION

HI 726 Checker®HC is supplied with sample cuvettes with caps (2 ea.), powder reagents for Nickel HR (6), battery and instructions.

REAGENTS AND STANDARDS

HI 726-25 Reagents for 25 tests (Nickel HR)
Calibration checking set

(0 and 3.50 Nickel HR)

ACCESSORIES

HI 731318 Cuvette cleaning cloth (4)
HI 731321 Glass cuvettes (4)
HI 731225 Caps for cuvettes (4)

HI 93703-50 Cuvette cleaning solution, 230 mL



Easier to use and more accurate than chemical test kits

Photometric method

±0.10 g/L ±5% of reading accuracy

0.01 g/L resolution (700 points)

Large, easy to read digits

Auto shut off

Dedicated to a single parameter

Designed to work with HANNA's powder reagents

Uses 10 mL glass cuvettes

Small size, big convenience

Weighing a mere 64 g (2.25 oz.), the Checker®HC easily fits into the palm of your hand or pocket

Use for quick and accurate on the spot analysis

One button operation: zero and measure

Operated by a single AAA battery

Ideal for:

Steel manufacturing, electroplating and electronics production

SPECIFICATIONS	HI 726 (Nickel HR)
Range	0.00 to 7.00 g/L
Resolution	0.01 g/L
Accuracy @ 25°C/77°F	±0.10 g/L ±5% of reading
Light Source	LED @ 575 nm
Light Detector	silicon photocell
Environment	0 to 50°C (32 to 122°F); RH max 95% non-condensing
Battery Type	1.5V AAA
Auto-off	after three minutes of non-use and ten seconds after reading
Dimensions	81.5 x 61 x 37.5 mm (3.2 x 2.4 x 1.5")
Weight	64 g (2.25 oz.)
Method	adaptation of the photometric method



With great products, come great results™

WE DESIGN, MANUFACTURE, SUPPLY AND SUPPORT ALL OF OUR PRODUCTS.

When you buy a HANNA product, you're not only buying the best value for your money, but you're also adding the benefit of HANNA's unsurpassed customer service and post-sale technical support. **That's 360° Value**.