

Rugged Fixed Analog Camera

AMZ-3041-2



- Indoor/outdoor fixed camera
- -40° to 60° range of operation
- 12 VDC and 24 VDC versions
- Wide dynamic range
- Certified for use in hazardous areas

High-resolution, compact video camera for harsh environments

The AMZ-3041-2 is a high quality, high-resolution, analog, day/night video camera with a vari-focal and auto iris-lens. A variety of lens options are available to suit any application.

The camera is housed in a heavy-duty, cast-aluminum, weatherproof enclosure suitable for hostile environments. The camera is sealed and certified for use in hazardous

areas. The complete assembly is rated NEMA 7/4x. A stainless-steel enclosure option is also available.

The AMZ-3041-2 is ready for mounting using the included mounting arm. The camera requires only power and a coax video connection. A separate video encoder is required to IP-enable this camera system.

► specifications

Imager	1/3" DPS CMOS
Minimum Illumination	0.3 Lux (color); 0.06 Lux (b/w)
White Balance	Auto
Auto Iris	DC iris
Gain	Auto
Horizontal Resolution	525 TV lines (NTSC) 625 TV lines (PAL)
S/N Ratio	50 dB (p-p/rms) or better
F-number	1.4
Video Output	VBS 1.0V p-p/75 Ohms
Weight	8.1 lbs. (Aluminum Enclosure) 10.2 lbs. (Stainless Steel Enclosure)
Voltage Required	12 VDC or 24 VDC
Power Consumption	0.7A @ 12 VDC 0.4A @ 24 VDC
Operating Temperature	-40° to 60° C
Storage Temperature	-45° to 65° C
Dimensions	5.50" H x 5.50" W x 7.75" D (Aluminum) 5.50" H x 5.50" W x 8" D (Stainless Steel)
Mount	Wall Mount Standard
Protection Class	NEMA Type 4x, IP66
Regulatory Approvals	
Safety	Conforms to UL STD 61010-1 + UL1203 Certified to CSA STD CSA22.2 NO.30 + CAN/CSA C22.2 No. 25 EN 60079-0:2012, EN 60079-1:2007, EN 60079-31:2009. ATEX 94/9/EC.

Hazardous Area
Class I Groups B, C & D,
Class II Groups E, F & G,
Class III Type 4x
Class I Zone 1 AEx d IIC
Ex d IIC IEC 60529, T6

► accessories

ACC-312	2.8-12 mm lens	31°-86° FOV
ACC-360	5-50 mm lens	6.5°-60° FOV
ACC-115-05	White LED ring	20' range
MB-100	Pole mount kit	
CT-4613	3/4" NPT C1D1 cable gland	

► features



Multiple lens options available



-40° to 60° C temperature range



Certified for use in hazardous areas

► ordering information

AMZ-3041-2-V-E

-E	Enclosure	
	Aluminum	
S	Stainless Steel	
-V	Voltage Required	
	12	12 VDC
	24D	24 VDC

► IVC camera management software

Point & click camera management & control

Robust, enterprise class software to manage and control your cameras and video from anywhere in the world.



**MADE IN THE
USA**

330 Nevada St., Newton, MA 02460 www.ivcco.com 617-467-3059

© 2017, Industrial Video & Control Co. The Industrial Video & Control Co. logo is a registered trademark of Industrial Video & Control Co.. All other company names and products are trademarks or registered trademarks of their respective companies. All information provided is subject to change without notice. 1/17/2017

IVC
&
**INDUSTRIAL
VIDEO & CONTROL**