

EC/TDS/Temp Pocket Tester VisionPlus EC330

Features

- Large display screen- displays conductivity/TDS and temperature at the same time.
- Dual range with selectable or auto-ranging options.
- 1 or 2 point calibration.
- Replaceable electrode module ensures extended usefulness.
- Battery life over 100 hours.
- Low battery indicator.
- IP67 waterproof housing.
- RoHS compliant.

New



Specifications

Range	Conductivity	0~1999uS/cm; 0~19.99mS/cm
	TDS	0~1000mg/L; 0~ 0.00g/L
	Temperature	0.0~99.5°C/ 32~212°F
Resolution	Conductivity	5uS; 0.05mS/cm
	TDS	5mg/L; 0.05g/L
	Temperature	0.5°C/ 1°F
Accuracy	Conductivity	±1%FS
	TDS	±1%FS
	Temperature	±0.5°C/ ±1°F
Temp Compensation	0.0 to 60.0°C	
Calibration	1 or 2 point (1415uS at 0~1999uS/cm range; 12.90mS at 0~19.99mS/cm range)	
Electrode Type / Cell Constant	Two wire conductivity cell / 1.0	
ATC	Thermistor, 10KΩ, at 25°C	
Display	LCD	
Power	LR44 x 4 batteries.	
Battery Life	>100 hours.	
Auto Power Off	After 10 minutes of inactivity.	
Case	IP-67 waterproof.	
Weight / Dimensions (W x D x H)	105 grams (Including batteries) /19.3cm x 4.4cm x 2.5cm	

Accessories

330P	Conductivity / TDS electrode module.
------	--------------------------------------