

EC/Resistivity/Temp Pocket Tester VisionPlus EC331

Features

- Large display screen- displays conductivity / Resistivity and temperature at the same time.
- Convenient one point calibration.
- SS316 stainless steel replaceable electrode module.
- Replaceable electrode module ensures extended usefulness.
- Battery life over 100 hours.
- Low battery indicator.
- IP67 waterproof housing.
- Temperature reading in \square and $^{\circ}\text{F}$, user selectable.
- RoHS compliant.

New



Specifications

Range	Conductivity	0.1~199.9uS
	Resistivity	1.0~20.0M Ω
	Temperature	0.0~99.5 \square / 32~212 $^{\circ}\text{F}$
Resolution	Conductivity	0.1uS
	Resistivity	0.1M Ω
	Temperature	0.5 \square / 1 $^{\circ}\text{F}$
Accuracy	Conductivity	$\pm 1\%$ FS
	Resistivity	$\pm 1\%$ FS
	Temperature	$\pm 0.5\mathbf{\square}$ / $\pm 1^{\circ}\text{F}$
Temp Compensation	0.0 to 60.0 \square	
Calibration	1 point (147uS at 0.1~199.9uS range)	
Electrode Type / Cell Constant	Two wire conductivity cell / 1.0	
ATC	Thermistor, 10K Ω , at 25 \square .	
Display	LCD	
Power	LR44 x 4 batteries.	
Battery Life	>100 hours.	
Auto Power Off	After 10 minutes of inactivity.	
Case	IP-67 waterproof.	
Weight / Dimensions (W x D x H)	105 grams (Including batteries) /193mm x 44mm x 25mm	

Accessories

331P	Conductivity / Resistivity electrode module.
------	--