

Anemomaster™ Model 6113/6114

High velocity (up to 50m/s), multi-function hot-wire Anemometer

Features:

- Simultaneous measurements of air velocity, air temperature, and differential pressure
- Large, easy to read LCD display
- Durable body
- The Model 6113 includes built-in printer
- Complete with probe with 79 in (200cm) cable, extension rod, shoulder strap, and 6 pcs. C cell batteries, and NIST Certificate



Specifications		
Model	6113	6114
Air Velocity Ranges	20 to 9840 fpm (0.10 to 50.0 m/s)	
Accuracy	+/- (3% of reading + 0.1 m/s)	
Temperature Ranges	32 to 212°F (0 to 100°C)	
Accuracy	+/- 2.0°F (1.0°C)	
Differential Pressure Ranges	+/- 5.00 kPa *Option	
Accuracy	+/- (3% of reading +0.01 kPa)	
Interface	RS232C	
Datalogging	100 measurements	
Analog Output	0 to 1 V *Option	
Built-in Printer	○	—
Power Supply	6 x C cell Batteries	
Dimensions	W7.9" x H5.9" x D3.9"	
Weight	2.2 lbs (1 kg)	



Accessories

- 6113-01: Spare Probe
- 6113-02: AC Adapter
- 6113-03: Extension Rod
- 6113-04: Shoulder Strap
- 6113-07: Pressure Sensor
- 6113-08: Analog Output

- S600-00: Data Processing Software
- 6000-02: Communication Cable to PC
- TP-202L: Rolled Printer Paper (10 rolls)