

Uncontrolled document as of August 20, 2009. Refer to website for up to date specifications.

# LIGHTS

## 2000 SabreLite



### SabreLite™ 2000 Flashlight

This powerful flashlight was designed with one thing in mind: SAFETY. It carries more approvals than any other flashlight on the market today, making it safe for any hazardous environment or condition. The SabreLite is o-ring sealed with a twist-on shroud and comes with a polarity battery guard tray that safeguards against dangerous "outgassing" of hydrogen from an accidentally reversed cell. It is powered by 3 C alkaline cells, submersible, and has an ABS resin body which resists chemicals, corrosion, and extreme temperatures. Unlike ordinary flashlights that produce a yellow beam, the SabreLite's incredibly bright Xenon lamp produces a powerful collimated white beam. Pelican's SabreLite is the leader in quality and performance.



Submersible

### NSN List

| NSN #            | Description        |
|------------------|--------------------|
| 6230-01-281-3775 | 2000B Black        |
| 6230-01-295-1259 | 2000B Yellow       |
| 6230-01-324-2951 | 2000B Orange       |
| 6230-01-496-3640 | 2000 Zone 1 (Peli) |

Minimum Pack 6 ea.

Packaged Weight: 6.8 oz.

Assorted Packs available - 2 black, 2 yellow, 2 orange.

### SabreLite™ 2000 Flashlight Configurations

| Cat. # | Description  |
|--------|--|
| 2000   | SabreLite™ 2000 Flashlight (Carded)                            |
| 2000PL | SabreLite™ 2000 Flashlight w/ Photoluminescent Shroud (Carded) |



Black



Orange



Yellow

### SabreLite™ 2000 Flashlight Specifications

| Light Source                | Tested Lumen Value | Tested Lux Value (@ 1 meter) |
|-----------------------------|--------------------|------------------------------|
| Xenon                       | 33.0               | 10,000                       |
| Batteries                   | Battery Burn Time  | Battery Pack/Charging Time   |
| 3 C Alkaline (Not included) | 5 hrs.             | N/A                          |
| Watts                       | Voltage            |                              |
| 3.3                         | 4.5                |                              |
| Length                      | Weight w/Batteries | Weight w/o Batteries         |
| 7.79" (19.8 cm)             | 12.8 oz. (0.36 kg) | 5.31 oz. (0.15 kg)           |

### SabreLite™ 2000 Flashlight Approvals

|  |  |
|--|--|
|  | Class I, Div. 2; Gp ABCD, T3C; Class II; Div. 2; Gp G.                           |
|  | Class I, II, Div. 2; Gp. ABCD/G, T3C.  |
|  | Listed 4S67/E184884 Class I, Div. 1; Gp.C, D / Class I; Zone 1; Gp.IIA; IIB; T3C |
|  | 10C-629-2  |
|  | IEC Ex TSA 06.0021X Ex ib e IIC T4 IP67  |

### SabreLite™ 2000 Flashlight Accessories

| Cat. # | Description                 | Sug. Retail |
|--------|-----------------------------|-------------|
| 2004   | SabreLite™ 2000 Lamp Module | US\$13.50   |

|        |                         |           |
|--------|-------------------------|-----------|
| 2003PL | Photoluminescent Shroud | US\$8.95  |
| 8052OR | Traffic Wand (Orange)   | US\$11.50 |
| 8052YW | Traffic Wand (Yellow)   | US\$11.50 |

**Pelican™ Products, Inc.**

23215 Early Avenue • Torrance, CA 90505 • Phone: (310) 326-4700 • (800) 473-5422 • Fax: (310) 326-3311  
e-mail: [sales@pelican.com](mailto:sales@pelican.com) • [www.pelican.com](http://www.pelican.com)