



Emergency Contact: Chemtrec (800) 424-9300
Or Norco (208) 336-1643

1125 West Amity Road
Boise, ID 83705
(208) 336-1643

Oxygen in Nitrogen 0.0001% to 5%

MATERIAL SAFETY DATA SHEET

Identification

Product Name: Oxygen in Nitrogen 0.0001% to 5%
Chemical Name: Oxygen in Nitrogen
Chemical Family: Gas Mixture
CAS Number: N/A
Common Names/Synonyms: N/A
MSDS Identification Code/Number: 2390
Prepared By: Quality Dept.

Revision Date: 03/14/01
Date Last Reviewed: 11/29/07

Composition, Information on Ingredients, Exposure Limits

Exposure Limits¹

Ingredient	% Volume	PEL-OSHA ²	TLV-ACGIH ³	LD ₅₀ or LC ₅₀ Route/Species
Oxygen Formula: O ₂ CAS: 7782-44-7 RTECS#: RS206000	0.0001 to 5	Not Applicable	Not Applicable	Not Available
Nitrogen Formula: N ₂ CAS: 7727-37-9 RTECS#: QW9700000	95 to 99.9999	None Established	Simple Asphyxiant	Not Available

¹ Refer to individual state or provincial regulations, as applicable, for limits that may be more stringent than those listed here.

² As stated in 29 CFR 1910, Subpart Z (revised July 1, 1993)

³ As stated in the ACGIH 2007 Threshold Limit Values for Chemical Substances and Physical Agents

OSHA Regulatory Status: This material is classified as hazardous under OSHA regulations.

Hazards Identification

Emergency Overview:

Odorless, colorless, nonflammable gas. Simple Asphyxiant – This product does not contain oxygen in sufficient quantities to support life and may cause asphyxia if released in a confined area. Maintain oxygen levels above 19.5%. Contents under pressure. Use and store below 125°F (52°C).

Route of Entry:

Skin Contact No	Skin Absorption No	Eye Contact No	Inhalation Yes	Ingestion No
--------------------	-----------------------	-------------------	-------------------	-----------------

Health Effects:

Exposure Limits No	Irritant No	Sensitization No
Teratogen No	Reproductive Hazard No	Mutagen No
Synergistic Effects None reported		

Hazards Identification Continued

Carcinogenicity: NTP: No IARC: No OSHA: No

Eye Effects:

Contact with rapidly expanding gas near the point of release may cause frostbite.

Skin Effects:

Contact with rapidly expanding gas near the point of release may cause frostbite with redness, skin color change to gray or white, and blistering.

Ingestion Effects:

None known. Ingestion is unlikely as product is a gas at room temperature.

Inhalation Effects:

Gas mixture does not contain sufficient oxygen to support life and acts as a non-toxic simple asphyxiant. Effects of oxygen deficiency resulting from simple asphyxiants may include: rapid breathing, diminished mental alertness, impaired muscular coordination, faulty judgment, depression of all sensations, emotional instability, and fatigue. As asphyxiation progresses, nausea, vomiting, prostration, and loss of consciousness may result, eventually leading to convulsions, coma, and death.

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

Medical Conditions Aggravated by Exposure:

None known.

NFPA Hazard Codes

Health: 0
Flammability: 0
Instability: 0

HMIS Hazard Codes

Health: 0
Flammability: 0
Physical Hazard: 3

Ratings System

0: No Hazard
1: Slight Hazard
2: Moderate Hazard
3: Serious Hazard
4: Severe Hazard

Hazard Ratings were assigned in accordance with Compressed Gas Association (CGA) guidelines as published in CGA Pamphlet P-19-2004, *CGA Recommended Hazard Ratings for Compressed Gases, 2nd Edition*.

First Aid Measures

Eyes:

None required for gas. If frostbite is suspected, flush eyes with cool water for 15 minutes and obtain immediate medical attention.

Skin:

None required for gas. For frostbite, immerse skin in lukewarm water. DO NOT USE HOT WATER. Obtain medical attention.

Ingestion:

None required.

Inhalation:

PROMPT MEDICAL ATTENTION IS MANDATORY IN ALL CASES OF OVEREXPOSURE. RESCUE PERSONNEL SHOULD BE EQUIPPED WITH SELF-CONTAINED BREATHING APPARATUS. Victims should be assisted to an uncontaminated area and inhale fresh air. Quick removal from the contaminated area is most important. Unconscious persons should be moved to an uncontaminated area and, if breathing has stopped, administer artificial resuscitation and supplemental oxygen. Further treatment should be symptomatic and supportive.

Fire Fighting Measures

Conditions of Flammability: Not flammable		
Flash Point: None	Method: Not Applicable	Autoignition Temperature: None
LEL % None		UEL % None
Hazardous Combustion Products: None		
Sensitivity to mechanical shock: None		
Sensitivity to static discharge: None		

Fire and Explosion Hazards:

Nonflammable. Cylinder may rupture violently from pressure when involved in a fire situation.

Extinguishing Media:

Use water spray to keep cylinders cool.

Fire Fighting Instructions:

If possible, stop the flow of gas supply. Use water spray to cool adjacent cylinders and areas. Fire fighters should wear a full-face piece NIOSH/MSHA approved self-contained breathing apparatus (SCBA) operated in positive pressure mode and full turnout gear.

Accidental Release Measures

Evacuate all personnel from affected area. Use appropriate protective equipment. If leak is in user's equipment, be certain to purge piping with inert gas prior to attempting repairs. If leak is in container or valve, contact the appropriate emergency telephone number listed in section 1 or call your closest Norco/NorLab location.

Handling and Storage

Electrical Classification:

Non-hazardous.

Gas mixture is non-corrosive and may be used with any common structural material.

Use only in well-ventilated areas. Valve protection caps must remain in place unless the cylinder is secured with valve outlet piped to use point. Do not drag, slide or roll cylinders. Use a suitable hand truck for cylinder movement. Use a pressure regulator when connecting cylinder to lower pressure (<3000 PSIG) piping or systems. Do not heat cylinder by any means to increase the discharge rate of product from the cylinder. Use a check valve or trap in the discharge line to prevent hazardous backflow into the cylinder.

Protect cylinders from physical damage. Store in cool, dry, well-ventilated area of non-combustible construction away from heavy traffic areas and emergency exits. Do not allow the temperature where cylinders are stored to exceed 125°F (52°C). Cylinders should be stored upright and firmly secured to prevent falling or being knocked over. Full and empty cylinders should be segregated. Use a "first in – first out" inventory system to prevent full cylinders from being stored for excessive periods of time.

For additional recommendations, consult Compressed Gas Association Pamphlets P-1 and Safety Bulletin SB-2.

Never carry a compressed gas cylinder or a container of a gas in cryogenic liquid form in an enclosed space such as a car trunk, van or station wagon. A leak can result in a fire, explosion, asphyxiation or a toxic exposure.

Exposure Controls, Personal Protection

Engineering Controls:

Use local exhaust to prevent accumulation of high concentrations and maintain atmospheric oxygen at or above 19.5%.

Eye/Face Protection:

Safety goggles or glasses as appropriate for the job.

Exposure Controls, Personal Protection Continued

Skin Protection:

Protective gloves of material appropriate for the job.

Respiratory Protection:

Positive pressure air line with full-face mask and escape bottle or self-contained breathing apparatus should be available for emergency use.

Other/General Protection:

Safety shoes.

Physical and Chemical Properties

Parameter	Value	Units
Physical state (gas, liquid, solid)	: Gas	
Vapor pressure	: Not Available	
Vapor density (Air = 1)	: 0.97	
Evaporation point	: Not Available	
Boiling point	: -320.4	°F
	: -195.8	°C
Freezing point	: -345.9	°F
	: -209.9	°C
pH	: Not Applicable	
Specific gravity	: Not Available	
Oil/water partition coefficient	: Not Available	
Solubility (H ₂ O)	: Very Slightly Soluble	
Odor threshold	: Not Applicable	
Odor and appearance	: Colorless, odorless gas	

Stability and Reactivity

Stability:

Stable

Incompatible Materials:

None

Hazardous Polymerization:

Does not occur.

Toxicological Information

Inhalation:

Product acts as a non-toxic simple asphyxiant. Does not contain sufficient oxygen to support respiration.

Reproductive:

Oxygen deficiency during pregnancy has produced developmental abnormalities in humans and experimental animals.

Ecological Information

Product does not contain Class I or Class II ozone depleting substances. Not toxic. Will not bioconcentrate.

Disposal Considerations

Do not attempt to dispose of waste or unused quantities in returnable cylinders. Return in the shipping container, *properly labeled, with any valve outlet plugs or caps secure and valve protection cap in place*, to Norco or NorLab for proper disposal. Non-refillable containers should be vented in a well-ventilated area then disposed of in accordance with local regulations, or returned to NorLab.

Transport Information

Parameter	United States DOT	Canada TDG
Proper Shipping Name:	Compressed gases, N.O.S., (Oxygen, Nitrogen)	Compressed gases, N.O. S.,
Hazard Class:	2.2	2.2
Identification Number:	UN 1956	UN 1956
Shipping Label:	Nonflammable Gas	Nonflammable Gas

Regulatory Information

SARA Title III Notifications and Information:

This product does not contain ingredients subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

SARA Title III – Hazard Classes:

Sudden Release of Pressure Hazard
Acute Health Hazard

California Proposition 65: This product does not contain any ingredient(s) known to the State of California that cause cancer or reproductive harm.

Other Information

ACGIH	American Conference of Governmental Industrial Hygienists
DOT	Department of Transportation
IARC	International Agency for Research on Cancer
NTP	National Toxicology Program
OSHA	Occupational Safety and Health Administration
PEL	Permissible Exposure Limit
SARA	Superfund Amendments and Reauthorization Act
STEL	Short Term Exposure Limit
TDG	Transportation of Dangerous Goods
TLV	Threshold Limit Value

Compressed gas cylinders shall not be refilled without the express written permission of the owner. Shipment of a compressed gas cylinder which has not been filled by the owner or with his/her (written) consent is a violation of transportation regulations.

Disclaimer of Expressed and Implied Warranties:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).