

# SaltTestr® 11

**Non-linear curve programmed for best results in testing NaCl in water applications**

**Factory calibrated against NaCl standards** – Ideal for testing salinity levels in pools

**±1% full-scale accuracy** – The best in its class!

**Full reading displayed** – No need to multiply the readout to obtain actual test values

**Automatic temperature compensation (ATC)** – Gives you accurate measurements even in fluctuating temperatures

**Waterproof, dustproof housing** – Meets IP67 ratings, plus—it floats!

**Replaceable electrode** – Reuse same meter body over and over again

**Push-button calibration** – Calibrate more precisely than trimpot adjustment—no screwdrivers necessary

**Hold function** – Freezes reading until you can log it

**Auto shutoff** – Saves your batteries

**Temperature display** – Selectable for °C or °F



**Calibration button tucked away in battery compartment to avoid accidental recalibration**



35662-52

ISO9001:2000  
CERTIFIED SUPPLIER

CE 1 year warranty

## Specifications

Model	SaltTestr 11
<b>Range</b>	0 to 10.00 ppt
<b>Resolution</b>	0.10 ppt
<b>Accuracy</b>	0.00 to 7.00 ppt: ±1% full-scale; above 7.00 ppt: ±3% full-scale
<b>Calibration standard range</b>	3 to 10.00 ppt*
<b>Calibration</b>	One point push-button calibration (using keys inside battery compartment)

\*For best accuracy, calibrate to 4.4 ppt NaCl with standard 00653-89 (order on page 45).

**Temperature display:** 0 to 50°C (32 to 122°F), 0.1°C resolution, ±0.5°C accuracy

**Operating temperature:** 0 to 50°C; 32 to 122°F

**Temperature compensation:** automatic (ATC) from 0 to 50°C (32 to 122°F)

**ATC coefficient:** 2% per °C, 1.11% per °F, 25°C reference temperature

**Wetted materials:** 316 stainless steel (electrodes) and Valox® housing

**Power and battery life:** four 1.5 V alkaline batteries Eveready A76 (included), 150 hrs continuous use (approx 600 tests per battery pack). Alternate replacement model LR44

### Dimensions

**Unit only:** 6½"L x 1½" dia (165 x 38 mm)

**Boxed:** 7¼" x 2¾" x 1⅞" (184 x 70 x 48 mm)

### Weight

**Unit only:** 3.25 oz (90 g); **Boxed:** 6.0 oz (170 g)

## Ordering Information

Catalog number	Description	Included
WD-35662-52	SaltTestr 11	Tester, protective plastic storage case, lanyard, and batteries

## Accessories

**WD-35661-17 Replacement electrode** for SaltTestr 11

**WD-35624-45 Vinyl carrying case** with belt loop; holds one tester and solution pouches

**WD-35653-15 Salt standard pouches**, 3000 ppm NaCl. Box of 20 pouches

**WD-09377-16 Replacement batteries**, 1.5 V. Pack of 6

**WD-35661-70 Deluxe calibration kit** includes two each calibration pouches (447 µS, 1413 µS, 2764 µS, 15,000 µS, and rinse water), sample jar, and foam-lined hard plastic carrying case. (Tester not included)



Fish Farms



Wastewater



Environmental Testing



Pools and Spas