

Acorn® Temp 6 RTD Thermometer

Our simplest RTD thermometer

Compact size – Fits right in your pocket—take your Oakton Temp 6 meter anywhere!

All push-button operation – For fast, easy use

Standard mini-three-pin connector – Accepts a variety of 100 Ω Pt 100 probes

Minimum and maximum temperature display – Displays highest/lowest temperature since meter was switched on, or use Min/Max Hold Mode to continuously update lowest/highest temperature

°C/°F selectable

Temperature offset calibration adjustment – Push-button adjustment for fine-tuning factory calibration

Hold function – Freezes measurements for convenient reading and recording

Auto-off function – Turns off meter after 17 minutes of nonuse to save batteries

Rubber armor – Protects meter and features a built-in stand



Rubber armor features built-in stand



General



Industrial

Select a probe to match your application

See page 82 for our wide selection of probes.

Specifications

Range: -250 to 1372°C (-418 to 2501°F)

Resolution: 0.1°C/°F from -99.9 to 299.9°C/°F; 1°C/°F outside this range

Accuracy: $\pm 0.25\%$ of reading plus 0.5°C (0.9°F) above -99.9°C/°F; $\pm 0.25\%$ of reading plus 1°C (2°F) below -99.9°C/°F

Display: single-line LCD, $\frac{7}{8}$ " high

Probe: one 100 Ω platinum RTD with mini-three-pin DIN connector (not included)

Power: four AAA batteries (included), for >200 hours continuous use

Dimensions: 5½" x 2¾" x 1⅝" (14 x 7 x 3.5 cm)

Weight: 0.9 lb (0.4 kg)

Ordering Information

Catalog number	Description	Included
WD-35626-20	Acorn Temp 6	Meter, rubber armor, and batteries
WD-85000-02	Calibrated meter kit	Meter, general-purpose probe (08117-70), NIST-traceable calibration report, rubber armor, and batteries

ISO9001:2000
CERTIFIED SUPPLIER



3 year
warranty
meter only