

# Temp 14 Thermistor Thermometer

## Rugged and reliable

**Standard bayonet connectors** – Choose from a wide variety of thermistor probes

**All push-button operation** – For fast, easy use

**Ergonomic design** – Easy to grip for one-handed operation

**°C/°F selectable**

**Minimum and maximum temperature display** – Displays highest/lowest temperature since meter was switched on, or use Min/Max Hold Mode to continuously update lowest/highest temperature

**Temperature offset calibration adjustment** – Push-button adjustment for fine-tuning factory calibration

**Hold function** – Freezes measurements for convenient reading and recording

**Auto-off function** – Turns off meter after 17 minutes of nonuse to save batteries

**Available rubber armor** – Protects meter and features a built-in stand

**PREDICTING  
A CHANGE IN  
TEMPERATURE**



35426-00 shown with available rubber armor



General-purpose  
QC research labs  
and biological  
process monitoring

Select a probe  
to match your  
application

See pages 83 and 87  
for our wide  
selection of probes.

## Specifications

**Range:** –40 to 302°F (–40 to 150°C)

**Resolution:** 0.01 or 0.1°C/°F

**Accuracy:**

From –40 to 125°C (–40 to 257°F): ±0.2°C (±0.4°F),

From 125 to 150°C (257 to 302°F): ±0.5°C (±0.9°F)

**Display:** 4-digit LCD (1/4" X 1/2" digits), 2 1/4" x 1 1/2" backlit viewing area

**Probe:** one 400-series thermistor (not included)

**Power:** three AA batteries (included) or optional AC adapter

**Battery life:** 700 hours continuous (without use of backlighting)

**Dimensions:**

**Meter:** 4" x 7" x 2" (10.2 x 18 x 5.2 cm)  
(with protective armor)

**Boxed:** 5 5/8" x 10 1/4" x 3" (13.5 x 26 x 7.5 cm)

**Weight:** Meter: 0.75 lb (0.4 kg); Boxed: 1.25 lb (0.6 kg)

## Ordering Information

Catalog number	Description	Included
WD-35426-00	Temp 14	Meter and batteries
WD-35426-01	Calibrated Temp 14	Meter and NIST-traceable calibration report
WD-35426-02	Calibrated system	Meter and NIST-traceable calibration report; probe sold separately
WD-35427-80	Rubber armor	Rubber armor with built-in meter stand
WD-35427-85	Hands-free kit	Multipurpose hanging strap and mounting magnets

WD-91427-99 AC power adapter

ISO9001:2000  
CERTIFIED SUPPLIER

CE

3 year  
warranty  
meter only