



# Temp 340 Datalogging Thermistor Thermometer

## Our most advanced thermistor thermometer

**Datalogging for up to 2000 points** – Time- and-date stamp for advanced data analysis

**Menu-driven setup and operation** – Detailed on-screen information makes the Temp 340 easy to use

**USB output** – Easily transfer stored readings to your computer

**Standard bayonet connectors** – Choose from a wide variety of thermistor probes

**All push-button operation** – For fast, easy use  
°C/°F selectable

**Minimum and maximum temperature display** – Displays highest/lowest temperature since meter was switched on, or use Min/Max Hold Mode to continuously update lowest/highest temperature

**Temperature offset calibration adjustment** – Push-button adjustment for fine-tuning factory calibration

**Hold function** – Freezes measurements for convenient reading and recording

**Auto-off function** – Turns off meter after 17 minutes of nonuse to save batteries

**Sealed keypad and ABS plastic case; available rubber armor** – Meet IP54 standards for splash resistance; armor adds protection and features a built-in stand



**PREDICTING  
A CHANGE IN  
TEMPERATURE**

35426-50 shown with available rubber armor



QC labs and research lab testing requiring GLP datalogging and analysis

Select a probe to match your application

See pages 83 and 87 for our wide selection of probes.

## Specifications

**Range:** -40.00 to 150.0°C (-40.00 to 302.0°F)

**Resolution:** 0.01 or 0.1°C/°F; auto-ranging to 0.1° above +99.99°

### Accuracy

From -40.00 to 99.99°C (-40.00 to 99.99°F):

±0.03°C (±0.06°F),

From 100.0 to 125.0°C (100.0 to 257.0°F): ±0.1°C (±0.1°F),

From 125.0 to 150.0°C (257.0 to 302.0°F): ±0.5°C (±0.9°F)

**Datalogging:** 2000 real-time readings, with time-and-date stamp

**Display:** 4-digit, custom dot matrix display; 1/4" x 1/2" digits, 2 1/4" x 1 1/2" backlit viewing area

**Probe:** two 400-series thermistor (not included)

**Power:** three AA batteries (included) or optional AC adapter

**Battery life:** 400 hours continuous (without use of backlighting)

### Dimensions:

**Meter:** 4" x 7" x 2" (10.2 x 18 x 5.2 cm) (with protective armor)

**Boxed:** 5 3/8" x 10 1/4" x 3" (13.5 x 26 x 7.5 cm)

**Weight: Meter:** 0.75 lb (0.4 kg); **Boxed:** 1.25 lb (0.6 kg)

## Ordering Information

Catalog number	Description	Included
WD-35426-50	Temp 340	Meter and batteries
WD-35426-51	Calibrated Temp 340	Meter and NIST-traceable calibration report
WD-35426-52	Calibrated system	Meter and NIST-traceable calibration report; probe sold separately
WD-35427-80	Rubber armor	Rubber armor with built-in meter stand
WD-35427-85	Hands-free kit	Multipurpose hanging strap and mounting magnets

WD-91427-99 AC power adapter

WD-35427-86 USB cable to connect to PC

ISO9001:2000  
CERTIFIED SUPPLIER



3 year  
warranty  
meter only